

# 屋内照明器具特性

品番 (品名)	S C 4 2 8	
光源	LDA3L-E17/C/W x1	280.0 lm
管理番号	K0158275(0)DB1	
BZ分類	BZ10	

器具効率	85%	天井	80%				70%				50%				30%				0%	
	上方光束		49%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	36%	床	10%				10%				10%				10%				0%	
室指数			照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	3.6	2.5	1.8	1.4	3.2	2.3	1.7	1.2	2.5	1.8	1.3	9	1.9	1.3	1.0	7	2
	中	0.6	0.8	4.3	3.2	2.5	2.0	3.8	2.9	2.2	1.8	3.0	2.3	1.8	14	2.3	1.7	1.3	10	4
	否	0.56	1.0	4.8	3.7	3.0	2.4	4.3	3.4	2.7	2.2	3.4	2.7	2.2	18	2.6	2.0	1.6	13	6
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	5.2	4.2	3.5	3.0	4.7	3.8	3.2	2.7	3.7	3.1	2.6	2.2	2.8	2.3	1.9	1.6	8
			1.5	5.6	4.7	4.0	3.4	5.0	4.2	3.6	3.1	4.0	3.4	2.9	2.5	3.0	2.6	2.2	1.9	9
取付高さ	器具間隔最大限		2.0	6.0	5.2	4.6	4.1	5.5	4.8	4.2	3.7	4.4	3.8	3.4	3.0	3.4	3.0	2.6	2.3	12
	横方向 (A)	縦方向 (B)	2.5	6.3	5.6	5.0	4.5	5.8	5.1	4.6	4.1	4.6	4.2	3.7	3.4	3.6	3.2	2.9	2.6	14
Hm	Hm	Hm	3.0	6.6	5.9	5.4	4.9	6.0	5.4	4.9	4.5	4.8	4.4	4.0	3.7	3.8	3.4	3.1	2.9	16
			4.0	6.9	6.3	5.9	5.4	6.3	5.8	5.4	5.0	5.1	4.7	4.4	4.1	4.0	3.7	3.5	3.2	19
			5.0	7.1	6.6	6.2	5.8	6.5	6.0	5.7	5.3	5.3	5.0	4.7	4.4	4.2	3.9	3.7	3.5	21
			7.0	7.3	7.0	6.6	6.3	6.7	6.4	6.1	5.8	5.5	5.2	5.0	4.8	4.4	4.2	4.0	3.8	24
			10.0	7.5	7.2	7.0	6.7	6.9	6.6	6.4	6.2	5.7	5.5	5.3	5.1	4.5	4.4	4.3	4.1	26

