

屋内照明器具特性	
品番 (品名)	S F 2 7 1 B Z
光源	LDA7L-G / Z60E / S / W / 2 × 1 810.0 l m
管理番号	K0127285 (1) DB 1
BZ分類	BZ9

器具効率	90 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	47 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	43 %		10 %				10 %				10 %				10 %				0 %	
室指数		照明率 (X0.01)																ZCM		
保守率	良	0.63	0.6	3.9	2.8	2.1	1.6	3.6	2.6	1.9	1.5	2.9	2.1	1.6	1.2	2.3	1.7	1.3	9	5
	中	0.6	0.8	4.7	3.6	2.8	2.3	4.2	3.3	2.6	2.1	3.4	2.7	2.1	1.7	2.7	2.1	1.7	14	7
	否	0.56	1.0	5.2	4.1	3.4	2.8	4.7	3.8	3.1	2.6	3.8	3.1	2.5	2.1	3.0	2.5	2.0	17	9
			1.25	5.7	4.7	3.9	3.3	5.2	4.3	3.6	3.1	4.2	3.5	3.0	2.5	3.3	2.8	2.4	20	12
下方投影面積		cm ²	1.5	6.0	5.1	4.4	3.8	5.5	4.7	4.0	3.5	4.5	3.9	3.3	2.9	3.6	3.1	2.7	2.3	14
等価発光面積		cm ²	2.0	6.5	5.7	5.0	4.5	6.0	5.2	4.6	4.1	4.9	4.3	3.9	3.5	3.9	3.5	3.1	2.8	17
取付高さ	器具間隔最大限		2.5	6.9	6.1	5.5	5.0	6.3	5.6	5.1	4.6	5.2	4.7	4.3	3.9	4.2	3.8	3.4	3.1	2.0
	横方向 (A)	縦方向 (B)	3.0	7.1	6.5	5.9	5.4	6.5	5.9	5.4	5.0	5.4	4.9	4.5	4.2	4.3	4.0	3.7	3.4	2.2
Hm	0.00Hm	0.00Hm	4.0	7.4	6.9	6.4	6.0	6.8	6.3	5.9	5.5	5.7	5.3	5.0	4.6	4.6	4.3	4.0	3.8	2.5
			5.0	7.6	7.2	6.7	6.3	7.0	6.6	6.2	5.9	5.9	5.5	5.2	5.0	4.8	4.5	4.3	4.1	2.7
			7.0	7.9	7.5	7.2	6.8	7.3	6.9	6.6	6.3	6.1	5.8	5.6	5.4	5.0	4.8	4.6	4.4	3.0
			10.0	8.1	7.8	7.5	7.3	7.5	7.2	7.0	6.7	6.3	6.1	5.9	5.7	5.2	5.0	4.9	4.7	3.3

