

# 屋内照明器具特性

品番 (品名)	PTSR10050KSP (1TOUBUN)														
光源	LED5000_70_77 x1 77.0 l m														
管理番号	K0155129 (0) DY1														
BZ分類	BZ2/0.9/BZ3/2.3/BZ4/4.5/BZ5														

器具効率	91 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	7 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	84 %		室指数	照明率 ( X0.01) ZCM																
保守率	良	0.69	0.6	60	51	45	41	58	50	45	41	56	49	44	40	54	47	43	40	38
	中	0.67	0.8	67	59	53	49	66	58	53	49	63	56	51	48	60	55	50	47	45
	否	0.63	1.0	72	64	59	54	70	63	58	54	67	61	57	53	64	59	55	52	50
			1.25	76	69	64	59	74	68	63	59	71	66	61	58	68	63	60	57	54
下方投影面積			1.5	79	72	67	63	77	71	66	62	74	68	64	61	70	66	63	60	57
等価発光面積			2.0	83	77	72	68	81	75	71	68	77	73	69	66	74	70	67	64	61
取付高さ	器具間隔最大限		2.5	85	80	76	72	83	78	74	71	79	75	72	69	76	73	70	67	64
	横方向 (A)	縦方向 (B)	3.0	86	82	78	75	85	80	77	74	81	77	74	72	77	75	72	70	66
H <sub>m</sub>	1.34 H <sub>m</sub>	0.38 H <sub>m</sub>	4.0	89	85	82	79	87	83	80	78	83	80	78	75	79	77	75	73	69
			5.0	90	87	84	81	88	85	82	80	84	82	80	78	81	79	77	75	71
			7.0	92	89	87	85	90	87	85	83	86	84	82	81	82	81	79	78	74
			10.0	93	91	89	88	91	89	88	86	87	86	85	83	84	83	82	80	76

