

屋内照明器具特性	
品番 (品名)	S F 9 9 8 Z
光源	LDA4L - H - E17 / E / S / W / 2 ×1 440.0 l m
管理番号	K0169410 (0) DR 1
B Z 分類	BZ10

器具効率	86 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	50 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	36 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.67 0.63 0.56	0.6	37	27	20	15	33	24	18	14	26	19	14	11	20	15	11	8	3	
		0.8	44	33	26	21	40	30	24	19	31	24	19	15	24	18	15	12	5	
		1.0	49	39	32	26	44	35	29	24	35	28	23	19	27	21	18	14	7	
		1.25	53	44	37	31	48	40	33	28	38	32	27	23	29	24	21	18	9	
下方投影面積	c m ²	1.5	57	48	41	36	51	44	37	32	41	35	30	26	31	27	23	20	11	
		2.0	62	54	48	42	56	49	43	39	45	40	35	31	35	31	27	24	13	
取付高さ	器具間隔最大限		2.5	65	58	52	47	59	53	48	43	47	43	39	35	37	33	30	27	16
	横方向 (A)	縦方向 (B)	3.0	67	61	55	51	61	55	51	46	49	45	41	38	38	35	32	30	17
H m	0.00 H m	0.00 H m	4.0	70	65	60	56	64	59	55	51	52	48	45	42	41	38	36	33	20
			5.0	72	67	63	60	66	62	58	55	54	51	48	45	42	40	38	36	32
			7.0	74	71	68	64	68	65	62	59	56	53	51	49	44	42	41	39	24
			10.0	76	74	71	69	70	67	65	63	58	56	54	52	46	45	43	42	27

