

屋内照明器具特性	
品番 (品名)	S NCX5 8 2 0 2
光源	LED6200_70_5499 x1 5499.0 lm
管理番号	K0181799(0)DR1
BZ分類	BZ6/1.1/BZ5/3.5/BZ6/4.5/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%					
	上方光束 26%		下方光束 74%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
室指数	照明率 ( X0.01 )																			ZCM				
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6				
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6				
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56				
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56				
下方投影面積	c m <sup>2</sup>		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0				
	等価発光面積		c m <sup>2</sup>																					
取付高さ	器具間隔最大限																							
	横方向 (A)	縦方向 (B)																						
1.5m	2.02m	1.95m	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0		
2	2.66	2.56	5.0	7.0	10.0	5.0	7.0	10.0	5.0	7.0	10.0	5.0	7.0	10.0	5.0	7.0	10.0	5.0	7.0	10.0	5.0	7.0	10.0	
2.5	3.32	3.19	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0
3	3.94	3.8	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0

