

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | S F 0 7 5 B                |
| 光源       | LED2700_70_185 ×1 185.0 lm |
| 管理番号     | K0158540(0)DR1             |
| BZ分類     | BZ10                       |

|        |                 |         |      |     |    |    |     |     |    |    |     |     |    |    |     |     |     |    |    |    |
|--------|-----------------|---------|------|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|-----|----|----|----|
| 器具効率   | 99%             | 反射率     | 天井   | 80% |    |    |     | 70% |    |    |     | 50% |    |    |     | 30% |     |    |    | 0% |
|        | 上方光束<br>99%     |         | 壁    | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10  | 70  | 50  | 30 | 10 | 0% |
| 下方光束   | 0%              | 床       | 10%  |     |    |    | 10% |     |    |    | 10% |     |    |    | 10% |     |     |    | 0% |    |
| 室指数    | 照明率 ( X 0.01 )  |         |      |     |    |    |     |     |    |    |     |     |    |    |     |     | ZCM |    |    |    |
| 保守率    | 良 0.67          | 0.6     | 43   | 33  | 26 | 21 | 36  | 28  | 23 | 19 | 25  | 19  | 16 | 13 | 14  | 11  | 9   | 8  | 0  |    |
|        | 中 0.63          |         | 51   | 41  | 34 | 29 | 43  | 35  | 29 | 25 | 29  | 24  | 21 | 18 | 17  | 14  | 12  | 10 | 0  |    |
|        | 否 0.56          |         | 56   | 47  | 40 | 35 | 48  | 40  | 35 | 31 | 32  | 28  | 24 | 22 | 18  | 16  | 14  | 13 | 0  |    |
| 下方投影面積 | cm <sup>2</sup> | 1.25    | 61   | 53  | 46 | 41 | 52  | 45  | 40 | 36 | 36  | 31  | 28 | 25 | 20  | 18  | 16  | 15 | 0  |    |
|        |                 | 1.5     | 65   | 57  | 51 | 46 | 55  | 49  | 44 | 40 | 38  | 34  | 31 | 28 | 22  | 20  | 18  | 17 | 0  |    |
| 等価発光面積 | cm <sup>2</sup> | 2.0     | 70   | 63  | 58 | 53 | 60  | 54  | 50 | 46 | 41  | 38  | 35 | 33 | 23  | 22  | 20  | 19 | 0  |    |
|        |                 | 2.5     | 73   | 67  | 62 | 58 | 62  | 58  | 54 | 51 | 43  | 40  | 38 | 36 | 25  | 23  | 22  | 21 | 0  |    |
| 取付高さ   | 器具間隔最大限         |         | 3.0  | 75  | 70 | 66 | 62  | 64  | 60 | 57 | 54  | 44  | 42 | 40 | 38  | 25  | 24  | 23 | 0  |    |
| Hm     | 横方向 (A)         | 縦方向 (B) | 4.0  | 77  | 74 | 70 | 67  | 67  | 64 | 61 | 58  | 46  | 44 | 42 | 41  | 27  | 26  | 25 | 0  |    |
|        | 0.20Hm          | 0.20Hm  | 5.0  | 79  | 76 | 73 | 70  | 68  | 66 | 63 | 61  | 47  | 46 | 44 | 43  | 27  | 27  | 26 | 0  |    |
|        |                 |         | 7.0  | 81  | 79 | 77 | 74  | 70  | 68 | 66 | 65  | 48  | 47 | 46 | 45  | 28  | 28  | 27 | 0  |    |
|        |                 |         | 10.0 | 83  | 81 | 79 | 78  | 71  | 70 | 69 | 67  | 49  | 49 | 48 | 47  | 29  | 28  | 28 | 0  |    |

