

屋内照明器具特性

品番 (品名)	S F 2 6 0 Z																					
光源	LDA7L - G / Z60E / S / W / 2 × 1 810.0 l m																					
管理番号	K0139356 (0) DB 1																					
BZ分類	BZ8																					
器具効率	79 %	天井	80 %				70 %				50 %				30 %				0 %			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	40 %	床	10 %				10 %				10 %				10 %				0 %			
下方光束	39 %	室指数	照明率 (X0.01) ZCM																			
保守率	良 中 否 0.63 0.6 0.56	0.6	36	26	20	16	33	24	18	14	27	20	15	12	22	16	13	10	6			
		0.8	42	33	26	21	39	30	24	20	32	25	20	17	26	20	17	14	8			
		1.0	47	38	31	26	43	35	29	24	35	29	24	21	28	24	20	17	11			
		1.25	51	43	36	31	47	39	34	29	39	33	28	24	31	27	23	20	13			
下方投影面積	cm ²	1.5	55	47	40	35	50	43	37	33	41	36	31	28	33	29	26	23	15			
		2.0	59	52	46	41	54	48	43	39	45	40	36	33	36	33	30	27	18			
器具間隔最大限	H m	0.00 H m	0.00 H m	2.5	62	56	50	46	57	51	47	43	47	43	39	36	39	35	32	20		
				3.0	64	58	54	49	59	54	50	46	49	45	42	39	40	37	35	32	22	
高さ	H m	0.00 H m	0.00 H m	4.0	67	62	58	54	61	57	54	50	52	48	46	43	42	40	38	24		
				5.0	68	64	61	58	63	60	56	53	53	50	48	46	44	42	40	38	26	
H m	0.00 H m	0.00 H m	0.00 H m	7.0	70	67	64	62	65	62	60	57	55	53	51	49	46	44	42	29		
				10.0	72	70	68	65	67	65	63	61	57	55	54	52	47	46	45	44	31	

