

# 屋内照明器具特性

品番 (品名)	SNCX51170										
光源	LED6200_70_5000 x1 5000.0 lm										
管理番号	K0170834(0)D 1										
BZ分類	BZ5										

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 ( X0.01) ZCM																	
保守率	良 中 否 0.63 0.6 0.56	0.6	56	44	36	31	55	43	36	31	53	42	35	30	50	41	35	30	28	
		0.8	66	55	47	41	65	54	46	41	62	53	46	41	60	51	45	40	38	
		1.0	73	62	54	49	71	61	54	48	68	60	53	48	66	58	52	48	45	
		1.25	79	69	62	56	77	68	61	56	74	66	60	55	71	65	59	55	53	
下方投影面積	cm <sup>2</sup>	1.5	83	74	67	62	82	73	67	62	78	71	66	61	76	69	64	60	58	
		2.0	89	81	75	70	87	80	75	70	84	78	73	69	81	76	72	68	66	
取付高さ	器具間隔最大限		2.5	93	86	81	76	91	85	80	76	88	83	78	75	85	81	77	74	71
	横方向 (A)	縦方向 (B)	3.0	95	89	85	80	93	88	84	80	90	86	82	79	88	84	81	78	75
Hm	1.29Hm	1.29Hm	4.0	98	94	90	86	97	93	89	86	94	90	87	84	91	88	85	83	80
			5.0	100	96	93	90	99	95	92	89	96	93	90	88	93	91	88	86	84
			7.0	102	100	97	95	101	98	96	94	98	96	94	92	96	94	92	91	88
			10.0	104	102	100	98	103	101	99	97	100	99	97	96	98	96	95	94	91

