

屋内照明器具特性

品番 (品名)	XAD11004K				
光源	LLD20004CQ1 ×1 531.0 lm				
管理番号	K0175550(0)DR1				
BZ分類	BZ4/0.7/BZ3				

器具効率	83%	天井	80%				70%				50%				30%				0%		
	上方光束 0%		反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
下方光束 83%	室指数	照明率 (X0.01) ZCM																			
保守率	良 中 否 0.67 0.63 0.56	0.6	51	41	35	31	50	41	35	31	48	40	35	31	46	39	34	31	29		
		0.8	59	51	45	41	58	50	45	41	56	49	44	40	54	48	44	40	39		
		1.0	65	57	52	48	64	57	51	47	62	55	51	47	60	54	50	47	45		
		1.25	70	63	58	54	69	62	57	54	66	61	57	53	64	60	56	53	51		
下方投影面積 等価発光面積	c m ² c m ²	1.5	73	67	62	58	72	66	62	58	69	65	61	58	67	63	60	57	55		
		2.0	77	72	68	65	76	71	68	64	74	70	66	64	72	68	65	63	61		
取付 高さ H m	器具間隔最大限		2.5	80	75	72	69	78	75	71	68	76	73	70	68	74	71	69	67	65	
	横方向 (A) 1.25 H m	縦方向 (B) 1.25 H m	3.0	81	78	75	72	80	77	74	71	78	75	73	70	76	74	71	70	68	
			4.0	83	81	78	76	82	80	77	75	80	78	76	74	78	76	75	73	71	
			5.0	85	82	80	78	84	81	79	78	81	80	78	76	79	78	77	75	73	
			7.0	86	84	83	81	85	83	82	81	83	82	80	79	81	80	79	78	76	
			10.0	87	86	85	84	86	85	84	83	84	83	82	81	82	81	81	80	78	

