

# 屋内照明器具特性

|         |                       |          |
|---------|-----------------------|----------|
| 品番 (品名) | PTSGB6030KSP(1TOUBUN) |          |
| 光源      | LED3000_70_220 ×1     | 220.0 lm |
| 管理番号    | K0168048(0)DY1        |          |
| BZ分類    | BZ1/2.3/BZ2           |          |

|        |             |                 |      |     |     |     |     |     |     |     |     |     |     |    |     |    |    |    |    |     |
|--------|-------------|-----------------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|----|----|----|-----|
| 器具効率   | 99%         | 天井              | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |    | 30% |    |    |    | 0% |     |
|        | 上方光束        |                 | 0%   | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10  | 70 | 50 | 30 | 10 | 0%  |
| 下方光束   | 99%         | 床               | 10%  |     |     |     | 10% |     |     |     | 10% |     |     |    | 10% |    |    |    | 0% |     |
| 室指数    | 照明率 (X0.01) |                 |      |     |     |     |     |     |     |     |     |     |     |    |     |    |    |    |    | ZCM |
| 保守率    | 良           | 0.69            | 0.6  | 78  | 71  | 66  | 63  | 77  | 70  | 66  | 63  | 75  | 70  | 66 | 63  | 74 | 69 | 65 | 63 | 61  |
|        | 中           | 0.67            | 0.8  | 83  | 77  | 72  | 69  | 83  | 76  | 72  | 69  | 81  | 75  | 72 | 69  | 79 | 74 | 71 | 68 | 67  |
|        | 否           | 0.63            | 1.0  | 87  | 81  | 77  | 73  | 86  | 80  | 76  | 73  | 84  | 79  | 76 | 73  | 82 | 78 | 75 | 72 | 71  |
| 下方投影面積 | 等価発光面積      | cm <sup>2</sup> | 1.25 | 90  | 85  | 81  | 77  | 89  | 84  | 80  | 77  | 87  | 83  | 79 | 76  | 85 | 82 | 78 | 76 | 74  |
|        |             |                 | 1.5  | 93  | 88  | 84  | 80  | 92  | 87  | 83  | 80  | 89  | 85  | 82 | 79  | 87 | 84 | 81 | 79 | 77  |
| 取付高さ   | 器具間隔最大限     |                 | 2.5  | 98  | 94  | 91  | 88  | 97  | 93  | 90  | 88  | 94  | 91  | 89 | 87  | 92 | 90 | 87 | 86 | 83  |
|        | 横方向 (A)     | 縦方向 (B)         | 3.0  | 99  | 96  | 93  | 90  | 98  | 95  | 92  | 90  | 96  | 93  | 91 | 89  | 93 | 91 | 89 | 88 | 85  |
| Hm     | 0.59Hm      | 0.23Hm          | 4.0  | 101 | 98  | 96  | 94  | 100 | 97  | 95  | 93  | 97  | 95  | 93 | 92  | 95 | 93 | 92 | 90 | 88  |
|        |             |                 | 5.0  | 102 | 100 | 98  | 96  | 101 | 99  | 97  | 95  | 98  | 97  | 95 | 94  | 96 | 95 | 93 | 92 | 90  |
|        |             |                 | 7.0  | 103 | 102 | 100 | 99  | 102 | 101 | 99  | 98  | 100 | 98  | 97 | 96  | 97 | 96 | 95 | 94 | 92  |
|        |             |                 | 10.0 | 104 | 103 | 102 | 101 | 103 | 102 | 101 | 100 | 101 | 100 | 99 | 98  | 99 | 98 | 97 | 96 | 94  |

