

屋内照明器具特性

品番 (品名)	XAD3 1 0 0 2 K				
光源	LLD4 0 0 0 2 CQ1 ×1		845.0 lm		
管理番号	K0175549 (0) DR 1				
BZ分類	BZ4 / 0.7 / BZ3				

器具効率	83 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	0 %	室指数																	照明率 (X0.01)																	ZCM																
下方光束	83 %																																																			
保守率	良 中 否	0.67	0.6	51	41	35	31	50	41	35	31	48	40	35	31	46	39	34	31	29																																
		0.63	0.8	59	51	45	41	58	50	45	41	56	49	44	40	54	48	44	40	39																																
			1.0	65	57	52	48	64	57	51	47	62	55	51	47	60	54	50	47	45																																
		0.56	1.25	70	63	58	54	69	62	57	54	66	61	57	53	64	60	56	53	51																																
下方投影面積	c m ²	1.5	73	67	62	58	72	66	62	58	69	65	61	58	67	63	60	57	55																																	
		2.0	77	72	68	65	76	71	67	64	74	70	66	64	72	68	65	63	61																																	
等価発光面積	c m ²	2.5	80	75	72	69	78	75	71	68	76	73	70	68	74	71	69	67	65																																	
		3.0	81	78	75	72	80	77	74	71	78	75	73	70	76	74	71	70	68																																	
取付高さ	器具間隔最大限		4.0	83	81	78	76	82	80	77	75	80	78	76	74	78	76	75	73	71																																
	横方向 (A)	縦方向 (B)	5.0	85	82	80	78	84	81	79	78	81	80	78	76	79	78	77	75	73																																
H m	1.25 H m	1.25 H m	7.0	86	84	83	81	85	83	82	81	83	82	80	79	81	80	79	78	76																																
			10.0	87	86	85	84	86	85	84	83	84	83	82	81	82	81	81	80	78																																

