

屋内照明器具特性	
品番 (品名)	XFL312VPF
光源	LDL40S.N/14/26(2600A) ×1 2600.0lm
管理番号	K0126759(5)DR1
BZ分類	BZ5

器具効率	61%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	61%																																																						
保守率	良 中 否	0.77	0.6	3.4	2.7	2.2	1.9	3.4	2.6	2.2	1.9	3.2	2.6	2.2	1.9	3.1	2.5	2.1	1.8	1.7																																			
		0.72	0.8	4.0	3.3	2.8	2.5	3.9	3.3	2.8	2.5	3.8	3.2	2.8	2.5	3.6	3.1	2.7	2.4	2.3																																			
			1.0	4.4	3.8	3.3	2.9	4.3	3.7	3.3	2.9	4.2	3.6	3.2	2.9	4.0	3.5	3.2	2.9	2.7																																			
		0.68	1.25	4.8	4.2	3.7	3.4	4.7	4.1	3.7	3.4	4.5	4.0	3.6	3.3	4.3	3.9	3.6	3.3	3.2																																			
下方投影面積	c m ²	1.5	5.1	4.5	4.1	3.7	4.9	4.4	4.0	3.7	4.7	4.3	4.0	3.7	4.6	4.2	3.9	3.6	3.5																																				
		2.0	5.4	4.9	4.5	4.2	5.3	4.9	4.5	4.2	5.1	4.7	4.4	4.1	4.9	4.6	4.3	4.1	3.9																																				
取付高さ	器具間隔最大限		2.5	5.6	5.2	4.9	4.6	5.5	5.1	4.8	4.5	5.3	5.0	4.7	4.5	5.1	4.9	4.6	4.4	4.2																																			
	横方向 (A)	縦方向 (B)	3.0	5.8	5.4	5.1	4.8	5.7	5.3	5.0	4.8	5.5	5.2	4.9	4.7	5.3	5.0	4.8	4.7	4.5																																			
1.5m	1.94m	2.13m	4.0	6.0	5.7	5.4	5.2	5.9	5.6	5.4	5.1	5.7	5.4	5.2	5.1	5.5	5.3	5.1	5.0	4.8																																			
2	2.57	2.68	5.0	6.1	5.8	5.6	5.4	6.0	5.8	5.6	5.4	5.8	5.6	5.4	5.3	5.6	5.5	5.3	5.2	5.0																																			
2.5	3.19	3.25	7.0	6.2	6.0	5.9	5.7	6.1	6.0	5.8	5.7	5.9	5.8	5.7	5.5	5.8	5.7	5.5	5.4	5.3																																			
3	3.81	3.84	10.0	6.3	6.2	6.1	5.9	6.2	6.1	6.0	5.9	6.1	6.0	5.9	5.8	5.9	5.8	5.7	5.7	5.5																																			

