

# 屋内照明器具特性

品番 (品名)	XAD3 1 8 1 4									
光源	LLD40404CQ1 (KAKUSAN) ×1 860.0 1m									
管理番号	K0183945 (0) DR 1									
BZ分類	BZ2									

器具効率	57 %	天井	80 %				70 %				50 %				30 %				0 %																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																				
		床	10 %				10 %				10 %				10 %				0 %																																				
上方光束	0 %	室指数																		照明率 ( X0.01 )																		ZCM																	
下方光束	57 %																																																						
保守率	良 中 否	0.67	0.6	3.8	3.3	2.9	2.6	3.8	3.2	2.9	2.6	3.6	3.2	2.9	2.6	3.5	3.1	2.8	2.6	2.5																																			
		0.63	0.8	4.4	3.9	3.5	3.3	4.3	3.8	3.5	3.3	4.2	3.8	3.5	3.3	4.1	3.7	3.5	3.3	3.2																																			
		0.56	1.0	4.7	4.3	4.0	3.7	4.7	4.3	4.0	3.7	4.5	4.2	3.9	3.7	4.4	4.1	3.9	3.7	3.6																																			
			1.25	5.0	4.6	4.4	4.1	5.0	4.6	4.3	4.1	4.8	4.5	4.3	4.1	4.7	4.4	4.2	4.1	4.0																																			
下方投影面積	c m <sup>2</sup>	1.5	5.2	4.9	4.6	4.4	5.1	4.8	4.6	4.4	5.0	4.7	4.5	4.3	4.9	4.7	4.5	4.3	4.2																																				
		2.0	5.5	5.2	5.0	4.8	5.4	5.1	4.9	4.8	5.3	5.0	4.9	4.7	5.1	4.9	4.8	4.7	4.5																																				
取付高さ	器具間隔最大限		2.5	5.6	5.4	5.2	5.0	5.5	5.3	5.1	5.0	5.4	5.2	5.1	4.9	5.3	5.1	5.0	4.9	4.8																																			
	横方向 (A)	縦方向 (B)	3.0	5.7	5.5	5.3	5.2	5.6	5.4	5.3	5.2	5.5	5.3	5.2	5.1	5.4	5.2	5.1	5.0	4.9																																			
H m	1.15 H m	1.15 H m	4.0	5.8	5.7	5.5	5.4	5.7	5.6	5.5	5.4	5.6	5.5	5.4	5.3	5.5	5.4	5.3	5.2	5.1																																			
			5.0	5.9	5.8	5.6	5.5	5.8	5.7	5.6	5.5	5.7	5.6	5.5	5.4	5.6	5.5	5.4	5.3	5.2	5.1																																		
			7.0	6.0	5.9	5.8	5.7	5.9	5.8	5.7	5.7	5.8	5.7	5.6	5.6	5.6	5.6	5.5	5.5	5.3																																			
			10.0	6.0	6.0	5.9	5.8	6.0	5.9	5.8	5.8	5.8	5.8	5.7	5.7	5.7	5.7	5.6	5.6	5.4																																			

