

屋内照明器具特性

| | | | | | | | | | | | | | | | |
|---------|-----------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XAS30834 | | | | | | | | | | | | | | |
| 光源 | LLD40404CQ1 (KAKUSAN) ×1 860.0 1m | | | | | | | | | | | | | | |
| 管理番号 | K0184330 (0) DR1 | | | | | | | | | | | | | | |
| BZ分類 | BZ3/0.7/BZ2 | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------|-----------------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率 | 50% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| | | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 上方光束 | 0% | 室指数 | | | | | | | | | | | | | | | | | | |
| 下方光束 | 50% | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | |
| | | ZCM | | | | | | | | | | | | | | | | | | |
| 保守率 | 良 | 0.67 | 0.6 | 3.3 | 2.8 | 2.5 | 2.3 | 3.2 | 2.8 | 2.5 | 2.3 | 3.1 | 2.7 | 2.4 | 2.2 | 3.1 | 2.7 | 2.4 | 2.2 | 2.2 |
| | 中 | 0.63 | 0.8 | 3.8 | 3.3 | 3.0 | 2.8 | 3.7 | 3.3 | 3.0 | 2.8 | 3.6 | 3.3 | 3.0 | 2.8 | 3.5 | 3.2 | 3.0 | 2.8 | 2.7 |
| | 否 | 0.56 | 1.0 | 4.1 | 3.7 | 3.4 | 3.2 | 4.0 | 3.7 | 3.4 | 3.2 | 3.9 | 3.6 | 3.4 | 3.2 | 3.8 | 3.5 | 3.3 | 3.2 | 3.1 |
| | | | 1.25 | 4.4 | 4.0 | 3.8 | 3.6 | 4.3 | 4.0 | 3.7 | 3.5 | 4.2 | 3.9 | 3.7 | 3.5 | 4.1 | 3.8 | 3.6 | 3.5 | 3.4 |
| 下方投影面積 | | cm ² | 1.5 | 4.5 | 4.2 | 4.0 | 3.8 | 4.5 | 4.2 | 4.0 | 3.8 | 4.4 | 4.1 | 3.9 | 3.7 | 4.2 | 4.0 | 3.9 | 3.7 | 3.6 |
| 等価発光面積 | | cm ² | 2.0 | 4.8 | 4.5 | 4.3 | 4.1 | 4.7 | 4.5 | 4.3 | 4.1 | 4.6 | 4.4 | 4.2 | 4.1 | 4.5 | 4.3 | 4.2 | 4.0 | 3.9 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 4.9 | 4.7 | 4.5 | 4.4 | 4.8 | 4.6 | 4.5 | 4.3 | 4.7 | 4.5 | 4.4 | 4.3 | 4.6 | 4.5 | 4.3 | 4.2 | 4.1 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 5.0 | 4.8 | 4.6 | 4.5 | 4.9 | 4.7 | 4.6 | 4.5 | 4.8 | 4.7 | 4.5 | 4.4 | 4.7 | 4.6 | 4.5 | 4.4 | 4.3 |
| Hm | 1.16Hm | 1.16Hm | 4.0 | 5.1 | 4.9 | 4.8 | 4.7 | 5.0 | 4.9 | 4.8 | 4.7 | 4.9 | 4.8 | 4.7 | 4.6 | 4.8 | 4.7 | 4.6 | 4.5 | 4.4 |
| | | | 5.0 | 5.1 | 5.0 | 4.9 | 4.8 | 5.1 | 5.0 | 4.9 | 4.8 | 5.0 | 4.9 | 4.8 | 4.7 | 4.9 | 4.8 | 4.7 | 4.7 | 4.5 |
| | | | 7.0 | 5.2 | 5.1 | 5.1 | 5.0 | 5.2 | 5.1 | 5.0 | 4.9 | 5.0 | 5.0 | 4.9 | 4.9 | 4.9 | 4.9 | 4.8 | 4.8 | 4.6 |
| | | | 10.0 | 5.3 | 5.2 | 5.2 | 5.1 | 5.2 | 5.2 | 5.1 | 5.1 | 5.1 | 5.1 | 5.0 | 5.0 | 5.0 | 4.9 | 4.9 | 4.9 | 4.7 |

