

屋内照明器具特性	
品番 (品名)	XFL326CB
光源	LDL40S.N/14/26(2600A) × 2 2600.0 1 m
管理番号	K0126766(1)DR1
BZ分類	BZ4

器具効率	87 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	87 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	5.2	4.2	3.5	3.1	5.1	4.1	3.5	3.1	4.9	4.0	3.5	3.1	4.7	3.9	3.4	3.0	2.9
	中	0.77	0.8	6.1	5.2	4.5	4.1	6.0	5.1	4.5	4.1	5.7	5.0	4.4	4.0	5.5	4.9	4.4	4.0	3.8
	否	0.68	1.0	6.7	5.8	5.2	4.8	6.6	5.8	5.2	4.7	6.3	5.6	5.1	4.7	6.1	5.5	5.1	4.7	4.5
			1.25	7.2	6.4	5.9	5.4	7.1	6.4	5.8	5.4	6.8	6.2	5.7	5.4	6.6	6.1	5.7	5.3	5.1
下方投影面積		cm ²	1.5	7.5	6.9	6.3	5.9	7.4	6.8	6.3	5.9	7.2	6.6	6.2	5.8	6.9	6.5	6.1	5.8	5.6
等価発光面積		cm ²	2.0	8.0	7.4	7.0	6.6	7.9	7.3	6.9	6.6	7.6	7.2	6.8	6.5	7.4	7.0	6.7	6.4	6.2
取付高さ	器具間隔最大限		2.5	8.3	7.8	7.4	7.1	8.1	7.7	7.3	7.0	7.9	7.5	7.2	6.9	7.7	7.4	7.1	6.8	6.6
	横方向 (A)	縦方向 (B)	3.0	8.5	8.1	7.7	7.4	8.3	8.0	7.6	7.3	8.1	7.8	7.5	7.2	7.9	7.6	7.4	7.1	6.9
1.5m	2.07 m	2.05 m	4.0	8.7	8.4	8.1	7.8	8.6	8.3	8.0	7.8	8.3	8.1	7.9	7.7	8.1	7.9	7.7	7.6	7.3
2	2.74	2.57	5.0	8.8	8.6	8.3	8.1	8.7	8.5	8.3	8.1	8.5	8.3	8.1	7.9	8.3	8.1	8.0	7.8	7.6
2.5	3.41	3.1	7.0	9.0	8.8	8.6	8.5	8.9	8.7	8.5	8.4	8.7	8.5	8.4	8.2	8.5	8.3	8.2	8.1	7.9
3	4.08	3.65	10.0	9.1	9.0	8.9	8.7	9.0	8.9	8.8	8.7	8.8	8.7	8.6	8.5	8.6	8.5	8.4	8.3	8.1

