

屋内照明器具特性

品番 (品名)	XFL326GA									
光源	LDL40S.N/14/26(2600A) ×2 2600.0 1m									
管理番号	K0126769(4)DR1									
BZ分類	BZ5/0.7/BZ4									

器具効率	83%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	83%																																																						
保守率	良 中 否	0.81	0.6	48	38	32	28	47	38	32	28	45	37	31	27	44	36	31	27	26																																			
		0.77	0.8	57	47	41	37	56	47	41	36	53	46	40	36	51	45	40	36	34																																			
			1.0	62	54	48	43	61	53	47	43	59	52	47	42	56	50	46	42	40																																			
		0.68	1.25	67	60	54	49	66	59	53	49	63	57	52	49	61	56	52	48	46																																			
下方投影面積	c m ²	1.5	71	64	58	54	69	63	58	54	67	61	57	53	65	60	56	53	51																																				
		2.0	75	69	65	61	74	69	64	60	71	67	63	60	69	65	62	59	57																																				
等価発光面積	c m ²	2.5	78	73	69	65	77	72	68	65	74	70	67	64	72	69	66	63	61																																				
		3.0	80	76	72	69	79	75	71	68	76	73	70	67	74	71	69	67	64																																				
取付高さ	器具間隔最大限		4.0	82	79	76	73	81	78	75	73	79	76	74	72	77	75	73	71	69																																			
	横方向 (A)	縦方向 (B)	5.0	84	81	79	76	83	80	78	76	81	78	76	75	78	77	75	73	71																																			
1.5m	2.04 m	2.13 m	7.0	86	84	82	80	85	83	81	79	82	81	79	78	80	79	78	74																																				
2	2.7	2.68	10.0	87	86	84	83	86	85	83	82	84	83	82	81	82	81	80	79	77																																			
2.5	3.36	3.25																																																					
3	4.02	3.84																																																					

