

屋内照明器具特性

品番 (品名)	XFL326KL									
光源	LDL40S.N/14/26(2600A) ×2 2600.0 1m									
管理番号	K0126770(5)DR1									
BZ分類	BZ4/0.7/BZ3/3.5/BZ4									

器具効率	74%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	74%																																																						
保守率	良 中 否	0.77	0.6	4.6	3.8	3.2	2.9	4.5	3.7	3.2	2.9	4.3	3.6	3.2	2.9	4.2	3.6	3.2	2.8	2.7																																			
		0.72	0.8	5.3	4.6	4.0	3.7	5.2	4.5	4.0	3.7	5.0	4.4	4.0	3.6	4.9	4.3	3.9	3.6	3.5																																			
		0.68	1.0	5.8	5.1	4.6	4.2	5.7	5.0	4.6	4.2	5.5	4.9	4.5	4.2	5.3	4.8	4.5	4.2	4.0																																			
			1.25	6.2	5.6	5.1	4.8	6.1	5.5	5.1	4.7	5.9	5.4	5.0	4.7	5.7	5.3	4.9	4.7	4.5																																			
下方投影面積		cm ²																																																					
等価発光面積		cm ²																																																					
取付高さ	器具間隔最大限																																																						
	横方向 (A)	縦方向 (B)																																																					
1.5m	1.81m	1.98m	4.0	7.4	7.2	6.9	6.7	7.3	7.1	6.9	6.7	7.1	6.9	6.7	7.0	6.8	6.6	6.5	6.3																																				
2	2.39	2.47	5.0	7.6	7.3	7.1	7.0	7.5	7.3	7.1	6.9	7.3	7.1	6.9	6.8	7.1	6.9	6.8	6.7																																				
2.5	2.97	2.98	7.0	7.7	7.5	7.4	7.2	7.6	7.4	7.3	7.2	7.4	7.3	7.2	7.1	7.2	7.1	7.0	6.9																																				
3	3.55	3.5	10.0	7.8	7.7	7.6	7.5	7.7	7.6	7.5	7.4	7.5	7.4	7.3	7.3	7.3	7.3	7.2	7.1																																				

