

屋内照明器具特性

品番 (品名)	XFL329BT									
光源	LDL40S.N/14/26(2600A) ×2					2600.0lm				
管理番号	K0126223(4)DB1									
BZ分類	BZ5									

器具効率	93%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	0%	室指数	照明率 (X0.01)																ZCM	
下方光束	93%																			
保守率	良 中 否	0.81	0.6	51	40	32	27	50	39	32	27	48	38	31	27	46	37	31	26	25
		0.77	0.8	61	50	42	36	59	49	42	36	57	48	41	36	54	46	40	36	34
		0.68	1.0	67	57	49	44	66	56	49	43	63	54	48	43	60	53	47	43	41
			1.25	73	63	56	51	71	63	56	51	68	61	55	50	66	59	54	50	48
下方投影面積	c m ²	1.5	77	68	62	56	75	67	61	56	72	66	60	55	70	64	59	55	53	
		2.0	82	75	69	65	81	74	69	64	78	72	68	63	75	70	66	63	60	
取付高さ	器具間隔最大限		2.5	86	80	75	70	84	79	74	70	82	77	73	69	79	75	71	68	66
	横方向 (A)	縦方向 (B)	3.0	88	83	78	75	87	82	78	74	84	80	76	73	81	78	75	72	70
1.5m	2.16m	2.16m	4.0	91	87	84	80	90	86	83	80	87	84	81	78	85	82	80	77	75
2	2.86	2.73	5.0	93	90	87	84	92	89	86	83	89	87	84	82	87	85	83	81	78
2.5	3.55	3.31	7.0	95	93	91	88	94	92	90	88	92	90	88	86	89	88	86	85	82
3	4.23	3.89	10.0	97	95	94	92	96	94	93	91	93	92	91	89	91	90	89	88	85

