

屋内照明器具特性	
品番 (品名)	XFL312VEX
光源	LDL40S.N/14/26(2600A) ×1 2600.0lm
管理番号	K0126416(1)DB1
BZ分類	BZ3/0.7/BZ2/8.5/BZ1

器具効率	71%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	71%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	47	39	35	32	46	39	35	32	45	38	34	31	43	38	34	31	30
	中	0.77	0.8	55	49	44	41	54	48	44	41	52	47	44	41	51	47	43	41	39
	否	0.68	1.0	60	54	50	47	59	54	50	47	57	53	49	47	56	52	49	47	45
			1.25	63	59	55	52	63	58	55	52	61	57	54	52	59	56	54	51	50
下方投影面積			1.5	66	62	58	56	65	61	58	56	63	60	57	55	62	59	57	55	53
			2.0	69	65	63	60	68	65	62	60	66	64	61	59	65	62	61	59	57
取付高さ	器具間隔最大限		2.5	71	68	65	63	70	67	65	63	68	66	64	62	66	65	63	62	60
	横方向 (A)	縦方向 (B)	3.0	72	69	67	65	71	69	67	65	69	67	66	64	68	66	65	63	62
1.5m	2.4m	2.1m	4.0	73	71	70	68	72	71	69	68	71	69	68	67	69	68	67	66	64
2	3.2	2.66	5.0	74	72	71	70	73	72	70	69	71	70	69	68	70	69	68	67	65
2.5	3.98	3.23	7.0	75	74	73	72	74	73	72	71	72	71	71	70	71	70	69	69	67
3	4.74	3.81	10.0	76	75	74	73	75	74	73	73	73	72	72	71	71	71	71	70	68

