

屋内照明器具特性

品番 (品名)	XFL323CB	
光源	LDL40S.N/14/26(2600A) ×2 2600.0 1m	
管理番号	K0126761(1)DR1	
BZ分類	BZ4	

器具効率	83%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	83%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	5.0	4.0	3.4	3.0	4.9	4.0	3.4	3.0	4.7	3.9	3.3	3.0	4.5	3.8	3.3	2.9	2.8
	中	0.77	0.8	5.8	4.9	4.3	3.9	5.7	4.9	4.3	3.9	5.5	4.8	4.2	3.9	5.3	4.7	4.2	3.8	3.7
	否	0.68	1.0	6.4	5.6	5.0	4.5	6.2	5.5	4.9	4.5	6.0	5.4	4.9	4.5	5.8	5.2	4.8	4.5	4.3
			1.25	6.8	6.1	5.6	5.2	6.7	6.0	5.5	5.1	6.5	5.9	5.5	5.1	6.3	5.8	5.4	5.1	4.9
下方投影面積		cm ²	1.5	7.2	6.5	6.0	5.6	7.0	6.4	6.0	5.6	6.8	6.3	5.9	5.5	6.6	6.1	5.8	5.5	5.3
等価発光面積		cm ²	2.0	7.6	7.1	6.6	6.3	7.5	7.0	6.6	6.2	7.2	6.8	6.5	6.2	7.0	6.7	6.4	6.1	5.9
取付高さ	器具間隔最大限		2.5	7.9	7.4	7.0	6.7	7.7	7.3	7.0	6.7	7.5	7.2	6.8	6.6	7.3	7.0	6.7	6.5	6.3
	横方向 (A)	縦方向 (B)	3.0	8.0	7.6	7.3	7.0	7.9	7.6	7.2	7.0	7.7	7.4	7.1	6.9	7.5	7.2	7.0	6.8	6.6
1.5m	2m	2.05m	4.0	8.3	8.0	7.7	7.4	8.2	7.9	7.6	7.4	7.9	7.7	7.5	7.3	7.7	7.5	7.3	7.2	7.0
2	2.65	2.56	5.0	8.4	8.2	7.9	7.7	8.3	8.1	7.8	7.6	8.1	7.9	7.7	7.5	7.9	7.7	7.6	7.4	7.2
2.5	3.29	3.1	7.0	8.6	8.4	8.2	8.0	8.5	8.3	8.1	8.0	8.2	8.1	8.0	7.8	8.0	7.9	7.8	7.7	7.5
3	3.93	3.65	10.0	8.7	8.6	8.4	8.3	8.6	8.5	8.3	8.2	8.4	8.3	8.2	8.1	8.2	8.1	8.0	7.9	7.7

