

屋内照明器具特性	
品番 (品名)	XFL323EY
光源	LDL40S.N/14/26(2600A) ×2      2600.0 1m
管理番号	K0126674(3)DB1
BZ分類	BZ3/0.7/BZ2

器具効率	72%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	72%																																																						
保守率	良 0.81 中 0.77 否 0.68	0.6	46	39	34	31	45	38	34	31	44	38	33	30	43	37	33	30	29																																				
		0.8	54	48	44	40	54	48	43	40	52	47	43	40	51	46	43	40	39																																				
		1.0	59	54	50	47	59	53	49	47	57	52	49	46	55	51	48	46	45																																				
		1.25	63	58	55	52	62	58	54	52	61	57	54	51	59	56	53	51	50																																				
下方投影面積	c m <sup>2</sup>	1.5	66	61	58	55	65	61	58	55	63	60	57	55	62	59	56	54	53																																				
		2.0	69	65	63	60	68	65	62	60	66	63	61	59	65	62	60	59	57																																				
等価発光面積	c m <sup>2</sup>	2.5	71	68	65	63	70	67	65	63	68	66	64	62	66	65	63	61	60																																				
		3.0	72	69	67	65	71	69	67	65	69	67	66	64	68	66	65	63	62																																				
取付高さ	器具間隔最大限		4.0	73	71	70	68	72	71	69	68	71	69	68	67	69	68	67	66	64																																			
	横方向 (A)	縦方向 (B)	5.0	74	73	71	70	73	72	71	69	72	70	69	68	70	69	68	67	65																																			
1.5m	2.37m	2.06m	7.0	75	74	73	72	74	73	72	71	73	72	71	70	71	70	69	67																																				
2	3.15	2.59	10.0	76	75	74	73	75	74	73	73	73	72	72	72	71	71	70	68																																				
2.5	3.92	3.15																																																					
3	4.68	3.71																																																					

