

屋内照明器具特性	
品番 (品名)	XFL323GA
光源	LDL40S.N/14/26(2600A) ×2      2600.0lm
管理番号	K0126764(1)DR1
BZ分類	BZ4

器具効率	81%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	81%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	48	38	32	28	47	38	32	28	45	37	31	28	43	36	31	28	26
	中	0.77	0.8	56	47	41	37	55	47	41	37	53	46	40	36	51	45	40	36	35
	否	0.68	1.0	61	53	47	43	60	53	47	43	58	51	47	43	56	50	46	42	41
			1.25	66	59	53	49	65	58	53	49	63	57	52	49	60	56	52	48	47
下方投影面積		cm <sup>2</sup>	1.5	69	63	58	54	68	62	57	53	66	61	56	53	64	59	56	53	51
等価発光面積		cm <sup>2</sup>	2.0	74	68	64	60	72	67	63	60	70	66	62	59	68	64	61	59	57
取付高さ	器具間隔最大限		2.5	76	72	68	65	75	71	67	64	73	69	66	63	71	68	65	63	61
	横方向 (A)	縦方向 (B)	3.0	78	74	71	68	77	73	70	67	75	72	69	66	73	70	68	66	64
1.5m	2.09m	2.15m	4.0	81	77	75	72	79	76	74	72	77	75	73	71	75	73	71	69	67
2	2.78	2.71	5.0	82	79	77	75	81	78	76	74	79	77	75	73	77	75	73	72	70
2.5	3.46	3.3	7.0	83	82	80	78	82	81	79	77	80	79	77	76	78	77	76	75	73
3	4.14	3.9	10.0	85	83	82	81	84	82	81	80	82	81	80	79	80	79	78	77	75

