

| | |
|----------|--------------------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | XFL323ZP |
| 光源 | LDL40S.N/29/31-9(3150A) ×2 3150.0 1m |
| 管理番号 | K0126763(1)DR1 |
| BZ分類 | BZ3/4.5/BZ4 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|-----------------|---------|-------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 73% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 0% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 73% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.86 | 0.6 | 46 | 38 | 33 | 29 | 45 | 38 | 33 | 29 | 43 | 37 | 32 | 29 | 42 | 36 | 32 | 29 | 28 |
| | 中 | 0.81 | 0.8 | 53 | 46 | 41 | 37 | 52 | 45 | 41 | 37 | 50 | 44 | 40 | 37 | 49 | 43 | 40 | 37 | 35 |
| | 否 | 0.76 | 1.0 | 58 | 51 | 46 | 43 | 57 | 50 | 46 | 42 | 55 | 49 | 45 | 42 | 53 | 48 | 45 | 42 | 41 |
| | | | 1.25 | 62 | 56 | 51 | 48 | 61 | 55 | 51 | 48 | 59 | 54 | 50 | 47 | 57 | 53 | 49 | 47 | 45 |
| 下方投影面積 | cm ² | | 1.5 | 64 | 59 | 55 | 51 | 63 | 58 | 54 | 51 | 61 | 57 | 53 | 51 | 59 | 56 | 53 | 50 | 49 |
| | 等価発光面積 | | 2.0 | 68 | 63 | 60 | 57 | 67 | 63 | 59 | 56 | 65 | 61 | 58 | 56 | 63 | 60 | 57 | 55 | 53 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 70 | 66 | 63 | 60 | 69 | 65 | 62 | 60 | 67 | 64 | 61 | 59 | 65 | 62 | 60 | 58 | 57 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 71 | 68 | 65 | 63 | 70 | 67 | 65 | 62 | 68 | 66 | 63 | 61 | 66 | 64 | 62 | 61 | 59 |
| 1.5m | 1.78m | 2.03m | 4.0 | 73 | 71 | 68 | 66 | 72 | 70 | 68 | 66 | 70 | 68 | 66 | 65 | 68 | 67 | 65 | 64 | 62 |
| 2 | 2.36 | 2.57 | 5.0 | 74 | 72 | 70 | 68 | 73 | 71 | 69 | 68 | 71 | 70 | 68 | 67 | 70 | 68 | 67 | 66 | 64 |
| 2.5 | 2.94 | 3.12 | 7.0 | 76 | 74 | 72 | 71 | 75 | 73 | 72 | 70 | 73 | 71 | 70 | 69 | 71 | 70 | 69 | 68 | 66 |
| 3 | 3.51 | 3.69 | 10.0 | 77 | 75 | 74 | 73 | 76 | 75 | 74 | 73 | 74 | 73 | 72 | 71 | 72 | 71 | 71 | 70 | 68 |

