

屋内照明器具特性

| | | | | | | | | | | |
|---------|--------------------------|--|--|--|--|----------|--|--|--|--|
| 品番 (品名) | XFL329BV | | | | | | | | | |
| 光源 | LDL40S.N/14/26(2600A) ×2 | | | | | 2600.0lm | | | | |
| 管理番号 | K0126223(4)DB1 | | | | | | | | | |
| BZ分類 | BZ5 | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|-------------|-----------------|------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 93% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| | | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 上方光束 | 0% | | | | | | | | | | | | | | | | | | | |
| 下方光束 | 93% | | | | | | | | | | | | | | | | | | | |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 中 否 | 0.81 | 0.6 | 51 | 40 | 32 | 27 | 50 | 39 | 32 | 27 | 48 | 38 | 31 | 27 | 46 | 37 | 31 | 26 | 25 |
| | | 0.77 | 0.8 | 61 | 50 | 42 | 36 | 59 | 49 | 42 | 36 | 57 | 48 | 41 | 36 | 54 | 46 | 40 | 36 | 34 |
| | | 0.68 | 1.0 | 67 | 57 | 49 | 44 | 66 | 56 | 49 | 43 | 63 | 54 | 48 | 43 | 60 | 53 | 47 | 43 | 41 |
| | | | 1.25 | 73 | 63 | 56 | 51 | 71 | 63 | 56 | 51 | 68 | 61 | 55 | 50 | 66 | 59 | 54 | 50 | 48 |
| 下方投影面積 | | cm ² | | | | | | | | | | | | | | | | | | |
| 等価発光面積 | | cm ² | | | | | | | | | | | | | | | | | | |
| 取付高さ | 器具間隔最大限 | | | | | | | | | | | | | | | | | | | |
| | 横方向 (A) | 縦方向 (B) | | | | | | | | | | | | | | | | | | |
| 1.5m | 2.16m | 2.16m | 4.0 | 91 | 87 | 84 | 80 | 90 | 86 | 83 | 80 | 87 | 84 | 81 | 78 | 85 | 82 | 80 | 77 | 75 |
| 2 | 2.86 | 2.73 | 5.0 | 93 | 90 | 87 | 84 | 92 | 89 | 86 | 83 | 89 | 87 | 84 | 82 | 87 | 85 | 83 | 81 | 78 |
| 2.5 | 3.55 | 3.31 | 7.0 | 95 | 93 | 91 | 88 | 94 | 92 | 90 | 88 | 92 | 90 | 88 | 86 | 89 | 88 | 86 | 85 | 82 |
| 3 | 4.23 | 3.89 | 10.0 | 97 | 95 | 94 | 92 | 96 | 94 | 93 | 91 | 93 | 92 | 91 | 89 | 91 | 90 | 89 | 88 | 85 |

