

# 屋内照明器具特性

品番 (品名)	NYY75033+NTS90150	
光源	LED3000_70_710 ×1	710.0 lm
管理番号	K0152455 (* ) DJ 1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	101%	床		10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																			ZCM
保守率	良 0.67	0.6	0.6	91	87	84	82	91	86	84	82	90	86	83	82	89	85	83	81	81
	中 0.63		0.8	96	92	89	87	95	91	89	87	94	91	88	87	93	90	88	86	85
	否 0.56		1.0	98	95	92	90	98	94	92	90	96	93	91	90	95	93	91	89	88
下方投影面積 等価発光面積	cm <sup>2</sup>	1.25	100	97	95	93	100	97	95	93	98	96	94	92	97	95	93	92	91	
		1.5	102	99	97	95	101	98	96	95	99	97	96	94	98	96	95	93	92	
		2.0	104	101	99	98	103	101	99	97	101	99	98	97	99	98	97	96	94	
取付高さ	器具間隔最大限		2.5	105	103	101	100	104	102	100	99	102	100	99	98	100	99	98	97	95
	横方向 (A)	縦方向 (B)	3.0	105	104	102	101	104	103	102	100	103	101	100	99	101	100	99	98	96
Hm	0.47Hm	0.47Hm	4.0	106	105	104	103	105	104	103	102	103	102	101	101	101	101	100	99	97
			5.0	107	106	105	104	106	105	104	103	104	103	102	102	102	101	101	100	98
			7.0	107	107	106	105	106	106	105	104	104	104	103	103	102	102	101	101	98
			10.0	108	107	107	106	107	106	106	105	105	104	104	103	103	102	102	102	99

