

屋内照明器具特性	
品番 (品名)	XL574WAFK
光源	XL574WAF ×1 3980.0 lm
管理番号	K0130721(7)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束		100%		床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM			
保守率	良	0.81	0.6	57	44	37	31	55	44	36	31	53	43	36	31	51	42	36	31	29			
	中	0.77	0.8	67	55	47	42	65	55	47	42	63	53	46	41	60	52	46	41	39			
	否	0.68	1.0	73	63	55	49	72	62	55	49	69	60	54	49	66	59	53	49	46			
			1.25	79	70	63	57	78	69	62	57	75	67	61	56	72	65	60	56	54			
下方投影面積 等価発光面積	c m ²		1.5	84	75	68	63	82	74	67	62	79	72	66	62	76	70	65	61	59			
	c m ²		2.0	89	82	76	71	88	81	75	71	85	79	74	70	82	77	73	69	67			
	器具間隔最大限		2.5	93	87	81	77	91	85	81	76	88	83	79	75	85	81	78	74	72			
取付高さ	横方向 (A)		縦方向 (B)	3.0	95	90	85	81	94	89	84	80	91	86	83	79	88	84	81	78	76		
	1.5m			1.94 m		1.95 m		4.0	98	94	90	87	97	93	89	86	94	91	88	85	91	89	86
2	2.58		2.59		5.0	100	97	93	90	99	95	92	90	96	93	91	88	93	91	89	87	84	
2.5	3.2		3.21		7.0	102	100	97	95	101	99	96	94	98	96	94	93	96	94	93	91	88	
3	3.84		3.85		10.0	104	102	100	99	103	101	99	98	100	99	97	96	98	96	95	94	91	

