

屋内照明器具特性

品番 (品名)	XL573PGVK														
光源	LED5000_85_4790 x1 4790.0 1 m														
管理番号	K0162374 (1) DB 1														
BZ分類	BZ4														

器具効率	99 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	0 %	室指数																		
下方光束	99 %	照明率 (X0.01)																		
		ZCM																		
保守率	良 中 否	0.81	0.6	5.9	4.7	3.9	3.4	5.7	4.6	3.9	3.4	5.5	4.5	3.9	3.4	5.3	4.4	3.8	3.4	3.2
		0.77	0.8	6.9	5.8	5.0	4.5	6.7	5.7	5.0	4.5	6.5	5.6	4.9	4.5	6.2	5.5	4.9	4.4	4.2
			1.0	7.5	6.5	5.8	5.3	7.4	6.5	5.8	5.3	7.1	6.3	5.7	5.2	6.9	6.2	5.6	5.2	5.0
		0.68	1.25	8.1	7.2	6.6	6.0	8.0	7.1	6.5	6.0	7.7	7.0	6.4	6.0	7.4	6.8	6.3	5.9	5.7
下方投影面積	c m ²	1.5	8.5	7.7	7.1	6.6	8.4	7.6	7.0	6.6	8.1	7.4	6.9	6.5	7.8	7.3	6.8	6.4	6.2	
		2.0	9.1	8.4	7.8	7.4	8.9	8.3	7.8	7.4	8.6	8.1	7.7	7.3	8.4	7.9	7.5	7.2	7.0	
取付高さ	器具間隔最大限		2.5	9.4	8.8	8.4	7.9	9.2	8.7	8.3	7.9	9.0	8.5	8.1	7.8	8.7	8.3	8.0	7.7	7.5
	横方向 (A)	縦方向 (B)	3.0	9.6	9.1	8.7	8.3	9.5	9.0	8.6	8.3	9.2	8.8	8.5	8.2	8.9	8.6	8.3	8.1	7.8
1.5m	1.84 m	1.84 m	4.0	9.9	9.5	9.2	8.9	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.7	9.2	9.0	8.8	8.6	8.3
2	2.43	2.43	5.0	10.1	9.8	9.5	9.2	9.9	9.7	9.4	9.1	9.7	9.4	9.2	9.0	9.4	9.2	9.0	8.9	8.6
2.5	2.96	2.96	7.0	10.3	10.1	9.8	9.6	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.4	9.7	9.5	9.4	9.2	9.0
3	3.55	3.56	10.0	10.4	10.3	10.1	10.0	10.3	10.1	10.0	9.9	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2

