

屋内照明器具特性	
品番 (品名)	XLF213PTNC(JYOUJI_CEILIN)
光源	LED5000_85_1500 x1 1500.0 lm
管理番号	K0152932(3)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	7%	床	10%				10%				10%				10%				0%			
下方光束	93%	室指数	照明率 (X0.01) ZCM																			
保守率	良 0.83	0.6	54	42	34	28	52	41	33	28	49	39	32	27	46	37	31	27	24			
	中 0.81	0.8	64	52	44	38	62	51	43	37	58	49	42	37	55	47	41	36	33			
	否 0.77	1.0	70	59	51	45	68	58	50	45	64	55	49	44	61	53	47	43	40			
			1.25	76	66	58	52	74	65	57	52	70	62	56	51	66	59	54	49	46		
下方投影面積	cm ²	1.5	80	71	64	58	78	69	63	57	74	66	61	56	70	64	59	54	51			
等価発光面積	cm ²	2.0	86	78	71	66	84	76	70	65	79	73	68	63	75	70	66	62	58			
取付高さ	器具間隔最大限		2.5	90	83	77	72	87	81	75	71	83	77	73	69	79	74	70	67	63		
	横方向 (A)	縦方向 (B)	3.0	92	86	81	76	90	84	79	75	85	81	76	73	81	77	74	71	66		
1.5m	1.82m	1.89m	4.0	95	90	86	82	93	88	84	81	89	85	81	78	85	81	79	76	71		
2	2.42	2.48	5.0	97	93	89	86	95	91	88	84	91	88	85	82	87	84	82	79	75		
2.5	3.03	3.07	7.0	100	97	94	91	98	95	92	89	93	91	89	86	89	87	85	84	79		
3	3.62	3.61	10.0	102	99	97	95	100	97	95	93	95	94	92	90	92	90	89	87	82		

