

屋内照明器具特性	
品番 (品名)	XLF213PTNK(JYOUJI_CEILIN)
光源	LED5000_85_1500 x1 1500.0lm
管理番号	K0152932(3)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																							
		床	10%				10%				10%				10%				0%																																							
上方光束	7%	室指数																			照明率 (X0.01)																			ZCM																		
下方光束	93%																																																									
保守率	良 中 否	0.83	0.6	5.4	4.2	3.4	2.8	5.2	4.1	3.3	2.8	4.9	3.9	3.2	2.7	4.6	3.7	3.1	2.7	2.4																																						
		0.81	0.8	6.4	5.2	4.4	3.8	6.2	5.1	4.3	3.7	5.8	4.9	4.2	3.7	5.5	4.7	4.1	3.6	3.3																																						
		0.77	1.0	7.0	5.9	5.1	4.5	6.8	5.8	5.0	4.5	6.4	5.5	4.9	4.4	6.1	5.3	4.7	4.3	4.0																																						
			1.25	7.6	6.6	5.8	5.2	7.4	6.5	5.7	5.2	7.0	6.2	5.6	5.1	6.6	5.9	5.4	4.9	4.6																																						
下方投影面積		cm ²																																																								
等価発光面積		cm ²																																																								
取付高さ	器具間隔最大限																																																									
	横方向 (A)	縦方向 (B)																																																								
1.5m	1.82m	1.89m	4.0	9.5	9.0	8.6	8.2	9.3	8.8	8.4	8.1	8.9	8.5	8.1	7.8	8.5	8.1	7.9	7.6	7.1																																						
2	2.42	2.48	5.0	9.7	9.3	8.9	8.6	9.5	9.1	8.8	8.4	9.1	8.8	8.5	8.2	8.7	8.4	8.2	7.9	7.5																																						
2.5	3.03	3.07	7.0	10.0	9.7	9.4	9.1	9.8	9.5	9.2	8.9	9.3	9.1	8.9	8.6	8.9	8.7	8.5	8.4	7.9																																						
3	3.62	3.61	10.0	10.2	9.9	9.7	9.5	10.0	9.7	9.5	9.3	9.5	9.4	9.2	9.0	9.2	9.0	8.9	8.7	8.2																																						

