


非常用照明器具特性




品番	XLF213PNNK(CEILING)		
名称			
光源	LED5000/97/425		
管理番号	K0177603(1)DR1		
光束	850mm x 1.00		
保守率	0.92		
適用品番	設計照度Eを得るための読取照度		
	E=2.0	E=1.0	E=0.5
XLF213PNNK(CEILING)	2.6	1.3	0.6
備考	非常点灯時の照度(30分後)		

直射水平面照度

ランプ光束1000lm

100 lx (x 10)

100 lx (x 10)



品番	XLF213PNNK(CEILING)				
名称					
光源	LED5000/97/425				
管理番号	K0177603(1)DR1				
光束	850.01m * 1.00			備考	非常点灯時の照度(30分後)
保守率	0.92				

非常灯配置表

器具取付高さ(m)		2.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6
単体配置	A1	5.4	5.6	5.7	5.8	5.9	6.0	6.1	6.2	6.3	6.4	6.5	6.6	6.7	6.8	7.0	7.1
	A'1	1.8	1.9	1.9	2.0	2.1	2.1	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.7	2.7	2.8
	B1	3.2	3.2	3.3	3.3	3.3	3.3	3.4	3.4	3.4	3.4	3.4	3.5	3.5	3.5	3.5	3.5
直線配置	A2	7.5	7.6	7.9	8.0	8.3	8.5	8.6	8.8	9.0	9.2	9.4	9.6	9.8	9.9	10.2	10.4
	B2	6.6	6.9	7.1	7.4	7.6	7.9	8.1	8.3	8.4	8.6	8.8	8.9	9.2	9.2	9.3	9.3
四角配置	A4	6.3	6.6	6.8	7.0	7.2	7.3	7.6	7.5	7.7	8.0	8.2	8.2	8.4	8.6	8.9	9.0
	B4	6.6	6.9	7.1	7.4	7.6	7.9	8.1	8.3	8.4	8.6	8.6	8.9	9.0	9.1	9.0	9.2
壁からの距離(最大)	A0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.1	1.0	1.0	1.2	1.4	1.4
	B0	2.6	2.6	2.5	2.6	2.6	2.7	2.7	3.0	2.9	2.9	2.9	3.1	3.1	3.1	3.0	3.1

器具取付高さ(m)		3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.4	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0
単体配置	A1	7.2	7.3	7.4	7.4	7.5	7.6	7.6	7.6	7.6	7.9	8.2	8.4	8.6	8.8	9.0	9.1
	A'1	2.9	2.9	3.0	3.1	3.1	3.2	3.2	3.3	3.4	3.6	3.9	4.2	4.4	4.6	4.8	4.9
	B1	3.5	3.5	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.7	3.7	3.8	3.8	3.7	3.7	3.6
直線配置	A2	10.6	10.8	11.0	11.2	11.3	11.5	11.6	11.8	11.9	12.5	13.1	13.8	14.4	14.9	15.5	16.0
	B2	9.4	9.4	9.4	9.5	9.5	9.6	9.6	9.6	9.6	9.8	9.9	10.1	10.2	10.4	10.5	10.5
四角配置	A4	9.2	9.4	9.6	9.8	10.0	10.2	10.4	10.6	10.8	11.8	12.8	13.7	14.4	14.9	15.5	16.0
	B4	9.3	9.3	9.4	9.4	9.5	9.5	9.6	9.6	9.6	9.8	9.9	10.0	10.1	10.3	10.5	10.5
壁からの距離(最大)	A0	1.4	1.6	1.6	1.6	1.8	1.8	1.9	1.9	2.0	2.4	2.6	2.8	3.0	3.0	2.8	2.3
	B0	3.1	3.1	3.1	3.1	3.1	3.1	3.0	3.0	3.0	2.8	2.1	1.2	1.2	1.0	1.2	1.1

器具取付高さ(m)		8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	12.5	13.0	13.5	14.0				
単体配置	A1	9.1	9.1	9.0	8.9	8.6	8.3	7.8	7.3	6.3	3.9	2.2	----				
	A'1	5.0	5.1	5.2	5.2	5.0	4.3	3.2	2.7	2.1	1.7	1.5	----				
	B1	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.8	2.6	2.4	1.9	----				
直線配置	A2	16.4	16.8	17.1	17.4	17.6	17.7	17.6	17.3	17.0	14.8	13.3	11.5				
	B2	10.6	10.4	10.3	10.2	10.0	9.8	9.5	9.2	8.8	8.5	8.3	8.0				
四角配置	A4	16.4	16.8	17.1	17.4	17.6	17.7	17.6	17.3	17.0	14.8	13.3	11.5				
	B4	10.6	10.4	10.3	10.2	10.0	9.8	9.5	9.2	8.8	8.5	8.3	8.0				
壁からの距離(最大)	A0	1.0	1.2	1.1	1.0	1.0	1.1	1.0	1.0	1.0	1.0	1.0	1.0				
	B0	1.3	1.3	1.1	1.3	1.2	1.3	1.3	1.2	1.2	1.2	1.2	1.0				

階段配置表

器具取付高さ(m)			1.0	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0
Y=1.0(m)	2.0Lx	X+	3.8	4.5	5.1	5.7	6.2	7.3	7.7	8.3	8.7	8.9
		X-	0.9	1.3	1.7	2.0	2.3	2.9	3.5	4.0	4.4	4.7
Y=1.5(m)	1.0Lx	X+	4.9	5.7	6.3	7.0	7.6	8.7	9.8	10.6	11.0	11.5
		X-	0.7	1.2	1.6	1.9	2.3	2.8	3.3	3.8	4.2	4.5
Y=2.0(m)	2.0Lx	X+	3.2	4.0	4.6	5.2	5.8	6.9	7.5	8.0	8.4	8.7
		X-	0.4	1.0	1.4	1.8	2.1	2.7	3.2	3.5	3.8	4.1
	1.0Lx	X+	4.5	5.3	6.0	6.6	7.3	8.4	9.5	10.4	10.8	11.3