

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XLF213PNNK(JYOUJI_WALL)      |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_1500 x1 1500.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0153253(2)DR1               |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ8/0.7/BZ7                  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                   |                 |      |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |
|--------|-------------------|-----------------|------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|----|----|
| 器具効率   | 100%              | 天井              | 80%  |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0% |    |
|        |                   | 壁               | 70   | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0% |    |
|        |                   | 床               | 10%  |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0% |    |
| 上方光束   | 24%               |                 |      |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |
| 下方光束   | 76%               |                 |      |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |
| 室指数    | 照明率 ( X0.01 ) ZCM |                 |      |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |
| 保守率    | 良<br>中<br>否       | 0.83            | 0.6  | 47 | 34 | 25 | 19  | 44 | 32 | 24 | 19  | 40 | 29 | 22 | 17  | 35 | 26 | 20 | 16 | 12 |
|        |                   | 0.81            | 0.8  | 56 | 43 | 34 | 28  | 53 | 41 | 33 | 27  | 47 | 37 | 30 | 25  | 42 | 33 | 27 | 23 | 18 |
|        |                   | 0.77            | 1.0  | 62 | 50 | 41 | 34  | 59 | 47 | 39 | 33  | 52 | 43 | 36 | 30  | 46 | 39 | 33 | 28 | 23 |
|        |                   |                 | 1.25 | 68 | 56 | 47 | 41  | 64 | 54 | 45 | 39  | 57 | 49 | 42 | 36  | 51 | 44 | 38 | 33 | 28 |
| 下方投影面積 |                   | cm <sup>2</sup> |      |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |
| 等価発光面積 |                   | cm <sup>2</sup> |      |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |
| 取付高さ   | 器具間隔最大限           |                 | 2.5  | 82 | 74 | 67 | 60  | 78 | 70 | 64 | 58  | 71 | 64 | 59 | 54  | 63 | 58 | 54 | 50 | 42 |
|        | 横方向 (A)           | 縦方向 (B)         | 3.0  | 85 | 77 | 71 | 65  | 81 | 74 | 68 | 63  | 73 | 68 | 63 | 58  | 66 | 62 | 57 | 54 | 46 |
| 1.5m   | 2.24m             | 1.9m            | 4.0  | 89 | 82 | 77 | 72  | 85 | 79 | 74 | 69  | 77 | 72 | 68 | 64  | 70 | 66 | 62 | 59 | 51 |
| 2      | 2.99              | 2.5             | 5.0  | 91 | 86 | 81 | 76  | 87 | 82 | 78 | 74  | 79 | 75 | 72 | 68  | 72 | 69 | 66 | 63 | 55 |
| 2.5    | 3.73              | 3.11            | 7.0  | 94 | 90 | 86 | 82  | 90 | 86 | 83 | 79  | 82 | 79 | 76 | 73  | 75 | 73 | 70 | 68 | 59 |
| 3      | 4.45              | 3.71            | 10.0 | 96 | 93 | 90 | 87  | 92 | 89 | 87 | 84  | 85 | 82 | 80 | 78  | 78 | 76 | 74 | 72 | 63 |

