

| 屋内照明器具特性 | |
|----------|-----------------------------|
| 品番 (品名) | XLF216NTNC(JYOUJI_WALL) |
| 光源 | LED5000_85_1550 x1 1550.0lm |
| 管理番号 | K0153255(5)DR1 |
| BZ分類 | BZ7 |

| | | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|------------------|------|------|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | |
| | 上方光束 | | 28% | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| | 下方光束 | | 72% | | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.83 | 0.6 | 48 | 36 | 27 | 22 | 46 | 34 | 26 | 21 | 40 | 31 | 24 | 19 | 36 | 27 | 22 | 18 | 14 | |
| | 中 | 0.81 | 0.8 | 57 | 45 | 36 | 30 | 54 | 42 | 35 | 29 | 48 | 38 | 31 | 26 | 42 | 34 | 29 | 24 | 19 | |
| | 否 | 0.77 | 1.0 | 63 | 51 | 43 | 36 | 59 | 49 | 41 | 35 | 53 | 44 | 37 | 32 | 46 | 39 | 34 | 29 | 24 | |
| | 下方投影面積 | c m ² | | 1.25 | 69 | 58 | 49 | 43 | 65 | 55 | 47 | 41 | 57 | 49 | 43 | 38 | 51 | 44 | 39 | 34 | 28 |
| 等価発光面積 | c m ² | | 1.5 | 73 | 62 | 54 | 48 | 69 | 59 | 52 | 46 | 61 | 53 | 47 | 42 | 54 | 48 | 43 | 38 | 31 | |
| | c m ² | | 2.0 | 78 | 69 | 62 | 56 | 74 | 66 | 59 | 53 | 66 | 59 | 54 | 49 | 59 | 53 | 49 | 45 | 37 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 82 | 74 | 67 | 61 | 78 | 70 | 64 | 59 | 70 | 64 | 58 | 54 | 62 | 57 | 53 | 49 | 41 | |
| | 横方向 (A) | 縦方向 (B) | | | | | | | | | | | | | | | | | | | |
| 1.5m | 2m | 1.91m | 4.0 | 88 | 82 | 77 | 72 | 84 | 79 | 74 | 69 | 76 | 71 | 67 | 63 | 68 | 64 | 61 | 58 | 49 | |
| 2 | 2.65 | 2.51 | 5.0 | 91 | 85 | 81 | 77 | 86 | 82 | 77 | 73 | 78 | 74 | 70 | 67 | 70 | 67 | 64 | 61 | 52 | |
| 2.5 | 3.32 | 3.11 | 7.0 | 93 | 89 | 86 | 82 | 89 | 85 | 82 | 79 | 81 | 78 | 75 | 72 | 73 | 70 | 68 | 66 | 56 | |
| 3 | 3.96 | 3.7 | 10.0 | 96 | 93 | 90 | 87 | 91 | 88 | 86 | 83 | 83 | 81 | 78 | 76 | 75 | 73 | 71 | 70 | 59 | |

