

屋内照明器具特性

品番 (品名)	XLF216NTNK(JYOUJI_WALL)														
光源	LED5000_85_1500 x1 1500.0lm														
管理番号	K0153253(2)DR1														
BZ分類	BZ8/0.7/BZ7														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	24%	室指数	照明率 (X0.01)																ZCM		
下方光束	76%																				
保守率	良 中 否	0.83	0.6	47	34	25	19	44	32	24	19	40	29	22	17	35	26	20	16	12	
		0.81	0.8	56	43	34	28	53	41	33	27	47	37	30	25	42	33	27	23	18	
		0.77	1.0	62	50	41	34	59	47	39	33	52	43	36	30	46	39	33	28	23	
			1.25	68	56	47	41	64	54	45	39	57	49	42	36	51	44	38	33	28	
下方投影面積	c m ²	1.5	72	61	53	46	68	58	51	44	61	53	46	41	55	48	42	38	32		
		2.0	78	69	61	54	74	66	58	52	67	60	54	49	60	54	49	45	38		
取付高さ	器具間隔最大限		2.5	82	74	67	60	78	70	64	58	71	64	59	54	63	58	54	50	42	
	横方向 (A)	縦方向 (B)	3.0	85	77	71	65	81	74	68	63	73	68	63	58	66	62	57	54	46	
1.5m	2.24m	1.9m	4.0	89	82	77	72	85	79	74	69	77	72	68	64	70	66	62	59	51	
2	2.99	2.5	5.0	91	86	81	76	87	82	78	74	79	75	72	68	72	69	66	63	55	
2.5	3.73	3.11	7.0	94	90	86	82	90	86	83	79	82	79	76	73	75	73	70	68	59	
3	4.45	3.71	10.0	96	93	90	87	92	89	87	84	85	82	80	78	78	76	74	72	63	

