

屋内照明器具特性

品番 (品名)	P T S G 0 9 0 3 0 K M S	
光源	LED3000_70_2640 ×1 2640.0 1 m	
管理番号	K0155130(0)DY1	
BZ分類	BZ1/4.5/BZ2	

器具効率	101%	天井	80%				70%				50%				30%				0%	
	上方光束 1%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 (X 0.01)																			ZCM
保守率	良 0.69	0.6	84	77	74	71	83	77	73	71	82	76	73	70	80	76	73	70	69	
	中 0.67		0.8	89	83	79	76	88	82	78	76	86	81	78	75	85	80	77	75	74
	否 0.63		1.0	92	86	82	79	91	86	82	79	89	85	81	79	87	83	81	78	77
下方投影面積	c m ²	1.25	95	89	86	83	93	89	85	82	91	87	84	82	90	86	84	81	80	
		1.5	97	92	88	85	95	91	88	85	93	90	87	84	91	88	86	84	82	
等価発光面積	c m ²	2.0	99	95	92	89	98	94	91	89	96	93	90	88	94	91	89	87	85	
		2.5	101	98	95	92	100	97	94	92	97	95	93	91	95	93	91	89	87	
取付高さ	器具間隔最大限		3.0	102	99	96	94	101	98	96	94	99	96	94	92	96	95	93	91	89
	横方向 (A)	縦方向 (B)	4.0	104	101	99	97	102	100	98	96	100	98	97	95	98	96	95	94	91
1.5m	0.45 m	0.86 m	5.0	105	103	101	99	103	102	100	98	101	100	98	97	99	98	96	95	93
2	0.58	0.9	7.0	106	104	103	101	105	103	102	101	102	101	100	99	100	99	98	97	94
2.5	0.7	0.94	10.0	107	106	104	103	106	104	103	102	103	102	101	101	100	99	99	99	96
3	0.82	1.01																		

