

屋内照明器具特性

品番 (品名)	LRD1010N	
光源	LED5000_70_432 x1	432.0 lm
管理番号	K0161908(1)DB1	
BZ分類	BZ2	

器具効率	100%	天井	80%				70%				50%				30%				0%				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	0%	反射率	床	10%				10%				10%				10%				0%			
下方光束	100%		室指数	照明率 (X0.01)																			
保守率	良	0.67	0.6	67	57	51	46	66	56	50	46	64	56	50	46	62	55	50	46	44			
	中	0.63	0.8	77	68	62	58	76	68	62	58	74	67	62	58	72	66	61	57	56			
	否	0.56	1.0	84	76	70	66	82	75	70	66	80	74	69	65	78	73	68	65	63			
			1.25	89	82	77	73	87	81	76	73	85	80	75	72	83	78	75	72	70			
下方投影面積		cm ²	1.5	92	86	81	78	91	85	81	77	88	84	80	77	86	82	79	76	74			
等価発光面積		cm ²	2.0	96	91	87	84	95	90	87	84	93	89	86	83	90	87	84	82	80			
取付高さ	器具間隔最大限		2.5	99	95	91	88	97	94	91	88	95	92	89	87	93	90	88	86	84			
	横方向 (A)	縦方向 (B)	3.0	100	97	94	91	99	96	93	91	97	94	92	90	94	92	90	88	86			
Hm	1.15Hm	1.15Hm	4.0	102	100	97	95	101	99	96	94	99	97	95	93	97	95	93	92	89			
			5.0	104	101	99	98	102	100	99	97	100	98	97	95	98	96	95	94	91			
			7.0	105	103	102	100	104	102	101	100	101	100	99	98	99	98	97	96	94			
			10.0	106	105	104	103	105	104	103	102	102	101	100	100	100	99	98	95	95			

