

屋内照明器具特性	
品番 (品名)	XLG201DGNK(JYOUJI)
光源	LED5000_85_830 x1 830.0 l m
管理番号	K0180341(0)D 1
BZ分類	BZ5

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																							
		床	10 %				10 %				10 %				10 %				0 %																																							
上方光束	3 %	室指数																			照明率 (X0.01)																			ZCM																		
下方光束	97 %																																																									
保守率	良 中 否	0.83	0.6	5.6	4.3	3.5	3.0	5.4	4.3	3.5	3.0	5.1	4.1	3.4	2.9	4.9	4.0	3.4	2.9	2.7																																						
		0.81	0.8	6.5	5.4	4.6	4.0	6.4	5.3	4.5	4.0	6.1	5.1	4.4	3.9	5.8	4.9	4.3	3.9	3.6																																						
		0.77	1.0	7.2	6.1	5.3	4.7	7.0	6.0	5.2	4.7	6.7	5.8	5.1	4.6	6.3	5.6	5.0	4.5	4.3																																						
			1.25	7.8	6.8	6.0	5.4	7.6	6.7	5.9	5.4	7.2	6.4	5.8	5.3	6.9	6.2	5.7	5.2	5.0																																						
下方投影面積		c m ²																																																								
等価発光面積		c m ²																																																								
取付高さ	器具間隔最大限																																																									
	横方向 (A)	縦方向 (B)																																																								
1.5m	1.93 m	1.93 m	4.0	9.7	9.2	8.8	8.4	9.5	9.0	8.6	8.3	9.1	8.8	8.4	8.1	8.8	8.5	8.2	7.9	7.6																																						
2	2.55	2.51	5.0	9.9	9.5	9.1	8.8	9.7	9.3	9.0	8.7	9.3	9.0	8.7	8.5	9.0	8.7	8.5	8.3	7.9																																						
2.5	3.19	3.11	7.0	10.1	9.8	9.5	9.2	9.9	9.6	9.4	9.1	9.6	9.3	9.1	8.9	9.3	9.1	8.9	8.7	8.3																																						
3	3.82	3.71	10.0	10.3	10.1	9.8	9.6	10.1	9.9	9.7	9.5	9.8	9.6	9.4	9.3	9.5	9.3	9.2	9.0	8.7																																						

