

屋内照明器具特性	
品番 (品名)	XLG201AGNC(JYOUJI)
光源	LED5000_85_830 x1 830.0 l m
管理番号	K0178167(0)D 1
BZ分類	BZ5

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	4 %	室指数																		
下方光束	96 %	照明率 (X0.01)																		
		ZCM																		
保守率	良 0.83 中 0.81 否 0.77	0.6	56	43	35	30	54	43	35	30	51	41	34	29	49	40	34	29	27	
		0.8	65	54	46	40	64	53	45	40	60	51	44	39	58	49	43	39	36	
		1.0	72	61	53	47	70	60	52	47	67	58	51	46	63	56	50	45	43	
		1.25	78	68	60	54	76	67	59	54	72	64	58	53	69	62	57	52	49	
下方投影面積	c m ²	1.5	82	73	65	60	80	71	65	59	76	69	63	58	73	67	62	57	54	
		2.0	87	80	73	68	85	78	72	67	82	76	70	66	78	73	69	65	62	
等価発光面積	c m ²	2.5	91	84	79	74	89	83	77	73	85	80	75	71	82	77	74	70	67	
		3.0	93	88	82	78	92	86	81	77	88	83	79	76	84	81	77	74	71	
取付高さ	器具間隔最大限		4.0	97	92	88	84	95	90	86	83	91	87	84	81	88	85	82	79	76
	横方向 (A)	縦方向 (B)	5.0	99	95	91	88	97	93	90	87	93	90	87	85	90	87	85	83	79
1.5m	1.93 m	1.93 m	7.0	101	98	95	92	99	96	94	91	96	93	91	89	92	91	89	87	83
2	2.55	2.51	10.0	103	101	98	96	101	99	97	95	98	96	94	93	95	93	92	90	87
2.5	3.19	3.11																		
3	3.82	3.71																		

