

屋内照明器具特性

品番 (品名)	XLG211DGNK(JYOUJI)	
光源	LED5000_85_1600 x1 1600.0lm	
管理番号	K0180341(0)D 1	
BZ分類	BZ5	

器具効率	100%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	3%	床	10%				10%				10%				10%				0%			
下方光束	97%	室指数	照明率 (X0.01) ZCM																			
保守率	良	0.83	0.6	5.6	4.3	3.5	3.0	5.4	4.3	3.5	3.0	5.1	4.1	3.4	2.9	4.9	4.0	3.4	2.9	2.7		
	中	0.81	0.8	6.5	5.4	4.6	4.0	6.4	5.3	4.5	4.0	6.1	5.1	4.4	3.9	5.8	4.9	4.3	3.9	3.6		
	否	0.77	1.0	7.2	6.1	5.3	4.7	7.0	6.0	5.2	4.7	6.7	5.8	5.1	4.6	6.3	5.6	5.0	4.5	4.3		
			1.25	7.8	6.8	6.0	5.4	7.6	6.7	5.9	5.4	7.2	6.4	5.8	5.3	6.9	6.2	5.7	5.2	5.0		
下方投影面積	cm ²		1.5	8.2	7.3	6.5	6.0	8.0	7.1	6.5	5.9	7.6	6.9	6.3	5.8	7.3	6.7	6.2	5.7	5.4		
等価発光面積	cm ²		2.0	8.7	8.0	7.3	6.8	8.5	7.8	7.2	6.7	8.2	7.6	7.1	6.6	7.8	7.3	6.9	6.5	6.2		
取付高さ	器具間隔最大限		2.5	9.1	8.4	7.9	7.4	8.9	8.3	7.8	7.3	8.5	8.0	7.6	7.2	8.2	7.7	7.4	7.0	6.7		
	横方向 (A)	縦方向 (B)	3.0	9.3	8.8	8.2	7.8	9.2	8.6	8.1	7.7	8.8	8.3	7.9	7.6	8.4	8.1	7.7	7.4	7.1		
1.5m	1.93m	1.93m	4.0	9.7	9.2	8.8	8.4	9.5	9.0	8.6	8.3	9.1	8.8	8.4	8.1	8.8	8.5	8.2	7.9	7.6		
2	2.55	2.51	5.0	9.9	9.5	9.1	8.8	9.7	9.3	9.0	8.7	9.3	9.0	8.7	8.5	9.0	8.7	8.5	8.3	7.9		
2.5	3.19	3.11	7.0	10.1	9.8	9.5	9.2	9.9	9.6	9.4	9.1	9.6	9.3	9.1	8.9	9.3	9.1	8.9	8.7	8.3		
3	3.82	3.71	10.0	10.3	10.1	9.8	9.6	10.1	9.9	9.7	9.5	9.8	9.6	9.4	9.3	9.5	9.3	9.2	9.0	8.7		

