

屋内照明器具特性

品番 (品名)	P M L C 0 9 5 0 W 2 S	
光源	LED5000_70_2150 ×1	2150.0 lm
管理番号	K0178471(0)DY1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 3%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	97%	床		10%				10%				10%				10%				0%
室指数	照明率 (X 0.01)																			ZCM
保守率	良	0.69	0.6	82	75	71	68	81	75	71	68	79	74	70	68	77	73	70	67	66
	中	0.67	0.8	87	82	78	75	86	81	77	74	84	80	77	74	83	79	76	74	72
	否	0.63	1.0	91	86	82	79	90	85	82	79	88	84	81	78	86	82	80	78	76
下方投影面積	等価発光面積	cm ²	1.25	94	90	86	83	93	89	85	83	91	87	84	82	89	86	83	81	79
			1.5	96	92	89	86	95	91	88	86	93	90	87	85	91	88	86	84	82
取付高さ	器具間隔最大限		2.0	99	96	93	90	98	95	92	90	95	93	90	89	93	91	89	87	85
	横方向 (A)	縦方向 (B)	2.5	101	98	95	93	99	97	94	93	97	95	93	91	94	93	91	90	87
1.5m	0.44m	0.92m	3.0	102	99	97	95	101	98	96	94	98	96	94	93	95	94	93	91	89
2	0.57	0.97	4.0	103	101	100	98	102	100	99	97	99	98	96	95	97	96	94	93	91
2.5	0.68	1.05	5.0	104	103	101	100	103	101	100	99	100	99	98	97	98	97	96	95	92
3	0.8	1.13	7.0	105	104	103	102	104	103	102	101	101	100	99	99	99	98	97	97	93
			10.0	106	105	104	104	105	104	103	103	102	101	101	100	99	99	98	98	94

