

屋内照明器具特性

| | | | | | | | | | | | | | | | | |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | NNN13510 | | | | | | | | | | | | | | | |
| 光源 | LED5000_70_1350 x1 1350.0 lm | | | | | | | | | | | | | | | |
| 管理番号 | K0180978(0)DR1 | | | | | | | | | | | | | | | |
| BZ分類 | BZ7/0.7/BZ6 | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | |
|------------------|--------------------------------------|---------|------------------|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|----|----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | |
| | | | 反射率 | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| | | | | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% |
| 上方光束 下方光束 | 43% 57% | 室指数 | 照明率 (X0.01) ZCM | | | | | | | | | | | | | | | | | | |
| 保守率 | 良 中 否 0.63 0.6 0.56 | 0.6 | 48 | 35 | 28 | 22 | 44 | 33 | 26 | 21 | 37 | 29 | 23 | 18 | 31 | 24 | 20 | 16 | 11 | | |
| | | 0.8 | 56 | 44 | 36 | 30 | 52 | 41 | 34 | 29 | 44 | 36 | 30 | 25 | 37 | 31 | 26 | 22 | 16 | | |
| | | 1.0 | 62 | 51 | 43 | 37 | 58 | 47 | 40 | 34 | 49 | 41 | 35 | 30 | 41 | 35 | 30 | 26 | 19 | | |
| | | 1.25 | 68 | 57 | 49 | 43 | 63 | 53 | 46 | 41 | 54 | 46 | 40 | 36 | 45 | 39 | 35 | 31 | 23 | | |
| 下方投影面積 等価発光面積 | c m ² c m ² | 1.5 | 72 | 62 | 54 | 48 | 67 | 58 | 51 | 45 | 57 | 50 | 45 | 40 | 48 | 43 | 38 | 35 | 26 | | |
| | | 2.0 | 77 | 69 | 62 | 56 | 72 | 64 | 58 | 53 | 62 | 56 | 51 | 47 | 52 | 48 | 44 | 40 | 30 | | |
| 取付 高さ | 器具間隔最大限 | | 2.5 | 81 | 73 | 67 | 62 | 75 | 69 | 63 | 58 | 65 | 60 | 55 | 51 | 55 | 51 | 47 | 44 | 34 | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 83 | 77 | 71 | 66 | 78 | 72 | 67 | 62 | 67 | 62 | 58 | 55 | 57 | 53 | 50 | 47 | 36 | |
| 1.5m | 1.96m | 1.91m | 4.0 | 87 | 81 | 76 | 72 | 81 | 76 | 72 | 68 | 70 | 66 | 63 | 60 | 60 | 57 | 54 | 52 | 40 | |
| 2 | 2.61 | 2.51 | 5.0 | 89 | 84 | 80 | 76 | 83 | 79 | 75 | 72 | 72 | 69 | 66 | 63 | 62 | 59 | 57 | 55 | 42 | |
| 2.5 | 3.27 | 3.12 | 7.0 | 91 | 88 | 84 | 81 | 86 | 82 | 79 | 77 | 75 | 72 | 70 | 67 | 64 | 62 | 60 | 59 | 45 | |
| 3 | 3.9 | 3.73 | 10.0 | 93 | 91 | 88 | 86 | 88 | 85 | 83 | 81 | 76 | 75 | 73 | 71 | 66 | 64 | 63 | 62 | 48 | |

