

屋内照明器具特性

品番 (品名)	NNN13511															
光源	LED4000_70_1320 x1 1320.0 lm															
管理番号	K0180978(0)DR1															
BZ分類	BZ7/0.7/BZ6															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	43%	室指数																			
下方光束	57%	照明率 (X0.01)																			
保守率	良 中 否	0.63 0.6 0.56	0.6	48	35	28	22	44	33	26	21	37	29	23	18	31	24	20	16	11	
			0.8	56	44	36	30	52	41	34	29	44	36	30	25	37	31	26	22	16	
下方投影面積	c m ²	1.25	68	57	49	43	63	53	46	41	54	46	40	36	45	39	35	31	23		
			1.5	72	62	54	48	67	58	51	45	57	50	45	40	48	43	38	35	26	
等価発光面積	c m ²	2.0	77	69	62	56	72	64	58	53	62	56	51	47	52	48	44	40	30		
			2.5	81	73	67	62	75	69	63	58	65	60	55	51	55	51	47	44	34	
取付高さ	器具間隔最大限		3.0	83	77	71	66	78	72	67	62	67	62	58	55	57	53	50	47	36	
	横方向 (A)	縦方向 (B)		4.0	87	81	76	72	81	76	72	68	70	66	63	60	60	57	54	52	40
1.5m	1.96m	1.91m	5.0	89	84	80	76	83	79	75	72	72	69	66	63	62	59	57	55	42	
2	2.61	2.51	7.0	91	88	84	81	86	82	79	77	75	72	70	67	64	62	60	59	45	
2.5	3.27	3.12	10.0	93	91	88	86	88	85	83	81	76	75	73	71	66	64	63	62	48	
3	3.9	3.73																			

