

# 屋内照明器具特性

品番 (品名)	XLG461RGN(JYOUJI)														
光源	LED5000_85_6680 x1 6680.0 lm														
管理番号	K0176624(0)DR1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	床	10%				10%				10%				10%				0%
下方光束	100%		室指数	照明率 ( X0.01) ZCM																
保守率	良 中 否	0.81	0.6	57	44	36	31	55	44	36	31	53	43	36	31	51	42	35	31	29
		0.77	0.8	67	55	47	41	65	54	47	41	62	53	46	41	60	52	45	41	39
			1.0	73	62	55	49	72	62	54	49	69	60	53	48	66	58	53	48	46
		0.68	1.25	79	70	62	56	78	69	62	56	75	67	61	56	72	65	60	55	53
下方投影面積	c m <sup>2</sup>	1.5	83	75	68	62	82	74	67	62	79	72	66	61	76	70	65	61	58	
		2.0	89	82	76	71	88	81	75	70	84	79	74	69	81	77	72	69	66	
取付高さ	器具間隔最大限		2.5	93	86	81	77	91	85	80	76	88	83	79	75	85	81	77	74	71
	横方向 (A)	縦方向 (B)	3.0	95	90	85	81	94	89	84	80	91	86	83	79	88	84	81	78	75
1.5m	1.99m	2.12m	4.0	98	94	90	87	97	93	89	86	94	91	88	85	91	88	86	84	81
2	2.63	2.67	5.0	100	97	94	91	99	96	93	90	96	93	91	88	93	91	89	87	84
2.5	3.27	3.23	7.0	103	100	98	95	101	99	96	94	98	96	95	93	96	94	93	91	88
3	3.91	3.82	10.0	104	102	101	99	103	101	100	98	100	99	97	96	98	97	95	94	91

