

屋内照明器具特性

品番 (品名)	XLGB1402	
光源	LLD40001CQ1 ×1	845.0 lm
管理番号	K0186480(0)DR1	
BZ分類	BZ5	

器具効率	66%	天井	80%				70%				50%				30%				0%		
	上方光束		3%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		63%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	3.6	2.8	2.3	1.9	3.5	2.8	2.3	1.9	3.3	2.7	2.2	1.9	3.2	2.6	2.2	1.9	1.7	
	中	0.63	0.8	4.3	3.5	3.0	2.6	4.2	3.4	2.9	2.6	3.9	3.3	2.9	2.5	3.7	3.2	2.8	2.5	2.3	
	否	0.56	1.0	4.7	4.0	3.5	3.1	4.6	3.9	3.4	3.0	4.3	3.8	3.3	3.0	4.1	3.6	3.2	2.9	2.7	
			1.25	5.1	4.4	3.9	3.6	5.0	4.4	3.9	3.5	4.7	4.2	3.8	3.5	4.5	4.0	3.7	3.4	3.2	
下方投影面積	c m ²		1.5	5.4	4.8	4.3	3.9	5.2	4.7	4.2	3.9	5.0	4.5	4.1	3.8	4.7	4.3	4.0	3.7	3.5	
	等価発光面積		c m ²	2.0	5.8	5.3	4.8	4.5	5.6	5.2	4.8	4.4	5.4	5.0	4.6	4.3	5.1	4.8	4.5	4.2	4.0
取付高さ	器具間隔最大限		2.5	6.0	5.6	5.2	4.9	5.9	5.5	5.1	4.8	5.6	5.3	5.0	4.7	5.4	5.1	4.8	4.6	4.4	
	横方向 (A)	縦方向 (B)	3.0	6.2	5.8	5.5	5.2	6.0	5.7	5.4	5.1	5.8	5.5	5.2	5.0	5.5	5.3	5.1	4.9	4.6	
H m	1.17 H m	1.17 H m	4.0	6.4	6.1	5.8	5.6	6.3	6.0	5.7	5.5	6.0	5.8	5.5	5.3	5.8	5.6	5.4	5.2	4.9	
			5.0	6.5	6.3	6.0	5.8	6.4	6.2	5.9	5.7	6.1	5.9	5.8	5.6	5.9	5.7	5.6	5.4	5.2	
			7.0	6.7	6.5	6.3	6.1	6.5	6.4	6.2	6.0	6.3	6.1	6.0	5.9	6.1	5.9	5.8	5.7	5.4	
			10.0	6.8	6.7	6.5	6.4	6.7	6.5	6.4	6.3	6.4	6.3	6.2	6.1	6.2	6.1	6.0	5.9	5.7	

