

屋内照明器具特性																							
品番 (品名)	XLGB1511																						
光源	LLD20003CQ1 ×1 531.0 lm																						
管理番号	K0186491 (0) DR 1																						
BZ分類	BZ5																						
器具効率	79 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
		床	10 %				10 %				10 %				10 %				0 %				
上方光束	3 %																						
下方光束	76 %																						
		室指数	照明率 (×0.01) ZCM																				
保守率	良 0.67 中 0.63 否 0.56	0.6	44	34	28	24	43	34	28	24	41	33	27	23	39	32	27	23	21				
		0.8	52	42	36	32	50	42	36	31	48	40	35	31	45	39	34	31	29				
		1.0	57	48	42	37	55	47	41	37	53	46	41	36	50	44	40	36	34				
		1.25	61	54	48	43	60	53	47	43	57	51	46	42	54	49	45	41	39				
下方投影面積	c m ²	1.5	65	58	52	47	63	57	51	47	60	55	50	46	57	53	49	45	43				
		2.0	69	63	58	54	68	62	57	54	65	60	56	52	62	58	54	52	49				
取付高さ	器具間隔最大限		2.5	72	67	62	59	70	66	62	58	68	63	60	57	65	61	58	56	53			
	横方向 (A)	縦方向 (B)	3.0	74	69	65	62	72	68	65	61	70	66	63	60	67	64	61	59	56			
H m	1.12 H m	1.12 H m	4.0	77	73	70	67	75	72	69	66	72	69	67	64	69	67	65	63	60			
			5.0	78	75	72	70	77	74	71	69	74	71	69	67	71	69	67	66	63			
			7.0	80	78	76	74	79	76	74	73	76	74	72	71	73	72	70	69	66			
			10.0	81	80	78	77	80	78	77	76	77	76	75	74	75	74	73	72	69			

配光曲線

ランプ光束1000lm

直射水平面照度

ランプ光束1000lm