

# 屋内照明器具特性

品番 (品名)	XFL323EX	
光源	LDL40S.N/14/26(2600A) ×2	2600.0lm
管理番号	K0127331(0)DB1	
BZ分類	BZ3/0.7/BZ2	

器具効率	72%	天井	80%				70%				50%				30%				0%					
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
	下方光束		72%		床	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																			ZCM				
保守率	良	0.81	0.6	4.6	3.9	3.4	3.1	4.6	3.8	3.4	3.1	4.4	3.8	3.3	3.0	4.3	3.7	3.3	3.0	2.9				
	中	0.77	0.8	5.5	4.8	4.4	4.0	5.4	4.8	4.4	4.0	5.2	4.7	4.3	4.0	5.1	4.6	4.3	4.0	3.9				
	否	0.68	1.0	6.0	5.4	5.0	4.7	5.9	5.4	5.0	4.7	5.7	5.3	4.9	4.7	5.6	5.2	4.9	4.6	4.5				
	下方投影面積	c m <sup>2</sup>		1.25	6.4	5.9	5.5	5.2	6.3	5.8	5.5	5.2	6.1	5.7	5.4	5.2	6.0	5.6	5.4	5.1	5.0			
等価発光面積	c m <sup>2</sup>		1.5	6.6	6.2	5.8	5.6	6.5	6.1	5.8	5.5	6.4	6.0	5.7	5.5	6.2	5.9	5.7	5.5	5.3				
	c m <sup>2</sup>		2.0	6.9	6.6	6.3	6.1	6.8	6.5	6.2	6.0	6.7	6.4	6.2	6.0	6.5	6.3	6.1	5.9	5.8				
取付高さ	器具間隔最大限		2.5	7.1	6.8	6.6	6.4	横方向 (A)		縦方向 (B)		7.0	6.8	6.5	6.3	6.8	6.6	6.4	6.3	6.7	6.5	6.3	6.2	6.0
	1.5m	2.41m						2.05m																
2	3.19	2.58	5.0	7.5	7.3	7.2	7.0	7.4	7.2	7.1	7.0	7.2	7.1	7.0	6.9	7.0	6.9	6.9	6.8	6.6				
2.5	3.97	3.13	7.0	7.6	7.4	7.3	7.2	7.5	7.4	7.3	7.2	7.3	7.2	7.1	7.1	7.1	7.1	7.1	7.0	6.9	6.8			
3	4.74	3.69	10.0	7.6	7.6	7.5	7.4	7.5	7.5	7.4	7.3	7.4	7.3	7.3	7.2	7.2	7.2	7.2	7.1	7.1	6.9			

