

屋内照明器具特性	
品番 (品名)	XFL323PF
光源	LDL40S.N/14/26(2600A) ×2      2600.0lm
管理番号	K0126762(5)DR1
BZ分類	BZ5

器具効率	64%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	64%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.77	0.6	3.6	2.9	2.3	2.0	3.6	2.8	2.3	2.0	3.4	2.7	2.3	2.0	3.3	2.7	2.3	2.0	1.8
		0.72	0.8	4.3	3.5	3.0	2.7	4.2	3.5	3.0	2.7	4.0	3.4	3.0	2.6	3.8	3.3	2.9	2.6	2.5
			1.0	4.7	4.0	3.5	3.1	4.6	4.0	3.5	3.1	4.4	3.8	3.4	3.1	4.2	3.7	3.4	3.1	2.9
		0.68	1.25	5.1	4.5	4.0	3.6	5.0	4.4	3.9	3.6	4.8	4.3	3.9	3.6	4.6	4.2	3.8	3.5	3.4
下方投影面積	c m <sup>2</sup>	1.5	5.4	4.8	4.3	4.0	5.2	4.7	4.3	4.0	5.0	4.6	4.2	3.9	4.8	4.5	4.1	3.9	3.7	
		2.0	5.7	5.2	4.8	4.5	5.6	5.2	4.8	4.5	5.4	5.0	4.7	4.4	5.2	4.9	4.6	4.4	4.2	
取付高さ	器具間隔最大限		2.5	5.9	5.5	5.2	4.9	5.8	5.4	5.1	4.8	5.6	5.3	5.0	4.8	5.4	5.2	4.9	4.7	4.5
	横方向 (A)	縦方向 (B)	3.0	6.1	5.7	5.4	5.1	6.0	5.7	5.4	5.1	5.8	5.5	5.3	5.0	5.6	5.4	5.2	5.0	4.8
1.5m	1.93m	2.13m	4.0	6.3	6.0	5.7	5.5	6.2	5.9	5.7	5.5	6.0	5.8	5.6	5.4	5.8	5.6	5.5	5.3	5.1
2	2.55	2.68	5.0	6.4	6.2	6.0	5.8	6.3	6.1	5.9	5.7	6.1	5.9	5.8	5.6	6.0	5.8	5.7	5.5	5.3
2.5	3.17	3.25	7.0	6.6	6.4	6.2	6.1	6.5	6.3	6.1	6.0	6.3	6.1	6.0	5.9	6.1	6.0	5.9	5.8	5.6
3	3.78	3.84	10.0	6.7	6.5	6.4	6.3	6.6	6.5	6.3	6.2	6.4	6.3	6.2	6.1	6.2	6.2	6.1	6.0	5.8

