

屋内照明器具特性	
品番 (品名)	XFL323ZP
光源	LDL40S.N/29/31-9(3150A) ×2 3150.0 1m
管理番号	K0126763(1)DR1
BZ分類	BZ3/4.5/BZ4

器具効率	73%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	73%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.86	0.6	46	38	33	29	45	38	33	29	43	37	32	29	42	36	32	29	28
	中	0.81	0.8	53	46	41	37	52	45	41	37	50	44	40	37	49	43	40	37	35
	否	0.76	1.0	58	51	46	43	57	50	46	42	55	49	45	42	53	48	45	42	41
			1.25	62	56	51	48	61	55	51	48	59	54	50	47	57	53	49	47	45
下方投影面積	cm ²		1.5	64	59	55	51	63	58	54	51	61	57	53	51	59	56	53	50	49
	等価発光面積		2.0	68	63	60	57	67	63	59	56	65	61	58	56	63	60	57	55	53
取付高さ	器具間隔最大限		2.5	70	66	63	60	69	65	62	60	67	64	61	59	65	62	60	58	57
	横方向 (A)	縦方向 (B)	3.0	71	68	65	63	70	67	65	62	68	66	63	61	66	64	62	61	59
1.5m	1.78m	2.03m	4.0	73	71	68	66	72	70	68	66	70	68	66	65	68	67	65	64	
2	2.36	2.57	5.0	74	72	70	68	73	71	69	68	71	70	68	67	70	68	67	66	
2.5	2.94	3.12	7.0	76	74	72	71	75	73	72	70	73	71	70	69	71	70	69	68	
3	3.51	3.69	10.0	77	75	74	73	76	75	74	73	74	73	72	71	72	71	71	70	

