

| | |
|----------|---|
| 屋内照明器具特性 | |
| 品番 (品名) | XFL326GA |
| 光源 | LDL40S.N/14/26(2600A) ×2 2600.0 1m |
| 管理番号 | K0126769(4)DR1 |
| BZ分類 | BZ5/0.7/BZ4 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|---------|--------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 83% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 0% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 83% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 中 否 | 0.81 | 0.6 | 48 | 38 | 32 | 28 | 47 | 38 | 32 | 28 | 45 | 37 | 31 | 27 | 44 | 36 | 31 | 27 | 26 |
| | | 0.77 | 0.8 | 57 | 47 | 41 | 37 | 56 | 47 | 41 | 36 | 53 | 46 | 40 | 36 | 51 | 45 | 40 | 36 | 34 |
| | | | 1.0 | 62 | 54 | 48 | 43 | 61 | 53 | 47 | 43 | 59 | 52 | 47 | 42 | 56 | 50 | 46 | 42 | 40 |
| | | 0.68 | 1.25 | 67 | 60 | 54 | 49 | 66 | 59 | 53 | 49 | 63 | 57 | 52 | 49 | 61 | 56 | 52 | 48 | 46 |
| 下方投影面積 | c m ² | 1.5 | 71 | 64 | 58 | 54 | 69 | 63 | 58 | 54 | 67 | 61 | 57 | 53 | 65 | 60 | 56 | 53 | 51 | |
| | | 2.0 | 75 | 69 | 65 | 61 | 74 | 69 | 64 | 60 | 71 | 67 | 63 | 60 | 69 | 65 | 62 | 59 | 57 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 78 | 73 | 69 | 65 | 77 | 72 | 68 | 65 | 74 | 70 | 67 | 64 | 72 | 69 | 66 | 63 | 61 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 80 | 76 | 72 | 69 | 79 | 75 | 71 | 68 | 76 | 73 | 70 | 67 | 74 | 71 | 69 | 67 | 64 |
| 1.5m | 2.04 m | 2.13 m | 4.0 | 82 | 79 | 76 | 73 | 81 | 78 | 75 | 73 | 79 | 76 | 74 | 72 | 77 | 75 | 73 | 71 | 69 |
| 2 | 2.7 | 2.68 | 5.0 | 84 | 81 | 79 | 76 | 83 | 80 | 78 | 76 | 81 | 78 | 76 | 75 | 78 | 77 | 75 | 73 | 71 |
| 2.5 | 3.36 | 3.25 | 7.0 | 86 | 84 | 82 | 80 | 85 | 83 | 81 | 79 | 82 | 81 | 79 | 78 | 80 | 79 | 78 | 77 | 74 |
| 3 | 4.02 | 3.84 | 10.0 | 87 | 86 | 84 | 83 | 86 | 85 | 83 | 82 | 84 | 83 | 82 | 81 | 82 | 81 | 80 | 79 | 77 |

