

屋内照明器具特性

品番 (品名)	XLF436NTNC(JYOUJI_WALL)	
光源	LED5000_85_3070 x1 3070.0 1m	
管理番号	K0153254(2)DR1	
BZ分類	BZ7	

器具効率	100%	天井	80%				70%				50%				30%				0%			
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
上方光束	28%	反射率	床	10%				10%				10%				10%				0%		
下方光束	72%		室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.83 0.81 0.77	0.6	48	36	27	22	46	34	26	21	40	31	24	19	36	27	22	18	14			
		0.8	57	45	36	30	54	42	35	29	48	38	32	26	42	34	29	24	20			
		1.0	63	51	42	36	60	49	41	35	53	44	37	32	47	39	34	29	24			
		1.25	69	58	49	43	65	55	47	41	58	49	43	38	51	44	39	34	28			
下方投影面積	c m ²	1.5	73	62	54	48	69	59	52	46	61	53	47	42	54	48	43	38	32			
		2.0	79	69	62	56	74	66	59	53	66	60	54	49	59	54	49	45	37			
取付高さ	器具間隔最大限		2.5	82	74	67	61	78	71	64	59	70	64	59	54	62	57	53	49	41		
	横方向 (A)	縦方向 (B)	3.0	85	78	71	66	81	74	68	63	72	67	62	58	65	60	56	53	45		
1.5m	2m	2.08m	4.0	88	82	77	72	84	79	74	69	76	71	67	64	68	64	61	58	49		
2	2.65	2.64	5.0	91	86	81	77	86	82	77	73	78	74	71	67	70	67	64	62	52		
2.5	3.29	3.21	7.0	93	89	86	82	89	85	82	79	81	78	75	72	73	71	68	66	56		
3	3.94	3.81	10.0	96	93	90	87	91	89	86	83	83	81	79	77	75	73	72	70	60		

