

屋内照明器具特性

品番 (品名)	XLGB78525									
光源	LED5000_70_710 x1					710.0 l m				
管理番号	K0165490(0)DB1									
BZ分類	BZ4/0.7/BZ3									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.67 0.63 0.56	0.6	61	50	43	37	60	49	42	37	58	48	42	37	56	47	41	37	35	
		0.8	72	61	54	49	70	61	54	49	68	59	53	49	65	58	53	49	47	
		1.0	78	69	62	57	77	68	62	57	74	67	61	57	72	65	60	56	54	
		1.25	84	76	70	65	83	75	69	65	80	74	68	64	78	72	68	64	62	
下方投影面積	c m ²	1.5	88	81	75	70	87	80	75	70	84	78	73	70	81	76	72	69	67	
		2.0	93	87	82	78	92	86	82	78	89	84	80	77	87	83	79	76	74	
取付高さ	器具間隔最大限		2.5	96	91	87	83	95	90	86	83	92	88	85	82	90	86	83	81	79
	横方向 (A)	縦方向 (B)	3.0	98	94	90	87	97	93	89	86	94	91	88	85	92	89	86	84	82
H m	1.25 H m	1.25 H m	4.0	101	97	94	92	99	96	94	91	97	94	92	90	94	92	90	88	86
			5.0	102	100	97	95	101	98	96	94	99	96	94	93	96	94	93	91	89
			7.0	104	102	100	98	103	101	99	98	100	99	97	96	98	97	95	94	92
			10.0	105	104	103	101	104	103	102	100	102	101	100	98	99	98	98	97	94

